
Aluminium Butt Hinges

Rising and Falling

Regular lubrication required. Fixings are not included: Fixing screw ordering information for these hinges are shown on page 38. Important: The logo shown indicates the type and size of screw required, which must be ordered separately







Discontinue

AFEI

Discontinued when stock = 0


Aluminium rising butt hinge

- Handed: Specify clockwise or anti-clockwise closing
- Maximum adjusted door weight 20 kg
- Hinge rises 13 mm at (180°)
- Door closes on release
- Galvanized steel pins and cams
- 10 year performance guarantee
- Not suitable for fire door applications due to low melting point
- Ideal for use in hospitals, veterinary surgeries where hosing down is necessary and hygiene is of paramount importance
- Polished anodised extruded aluminium
- Note: Only 2 hinges per door leaf are required


Length x width	(76 x	68 mm)
Closing direction	Clockwise	Anti-clockwise
Cat. No.	926.92.020	926.92.021

Order qty: 1 pc

Catalogue shows 90° mm Correct dimension is







Catalogue shows 90° mm Correct dimension is

B Aluminium rising butt hinge

- Handed: Specify clockwise or anti-clockwise closing
- Maximum adjusted door weight 40 kg
- Hinge rises 13 mm at (180°)
- Door **closes** on release Galvanized steel pins and cams
- Not suitable for fire door applications due to low melting point
- Ideal for use in hospitals, veterinary surgaries where hosing down is necessary and hygene is of paramount importance
- Polished anodised extruded aluminium
- Note: Only 2 hinges per door leaf are required

Length x width	102 >	70 mm
Closing direction	Clockwise	Anti-clockwise
Cat. No	+ .926.92.030	+ 926.92.031

Order qty: 1 pc

\bigoplus 1 1 102 \bigoplus 1 Ø 14

Ø 14



Clockwise closing shown

C Aluminium falling butt hinge


- Handed: Specify clockwise or anti-clockwise closing
- Maximum adjusted door weight 20 kg
- Hinge falls 13 mm at (180°)
- Door **opens** on release
- Galvanized steel pins and cams
- 10 year performance guarantee
- Not suitable for fire door applications due to low melting point
- Ideal for use in hospitals, veterinary surgaries where hosing down is necessary and hygene is of paramount importance
- Polished anodised extruded aluminium
- Note: Only 2 hinges per door leaf are required

Length x width	76 x 65 mm	
Closing direction	Clockwise	Anti-clockwise
Cat. No.	926.92.120	926.92.121

Order qty: 1 pc

TCH-AI 2008, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.

Catalogue shows 90° mm Correct dimension is










Anti-clockwise closing shown

D Aluminium falling butt hinge

- Handed: Specify clockwise or anti-clockwise closing
- Maximum adjusted door weight 40 kg
- Hinge falls 13 mm at 180°
 - Door **opens** on release
- Galvanized steel pins and cams
- Not suitable for fire door applications due to low melting point
- Ideal for use in hospitals, veterinary surgaries where hosing down is necessary and hygene is of paramount importance
- Polished anodised extruded aluminium
- Note: Only 2 hinges per door leaf are required

Length x width	102 x	70 mm
Closing direction	n Clockwise	Anti-clockwise
Cat. No.	+ 926.92.130	• .9 26.92.13 1

Order qty: 1 pc



20.11.14/3*



