# Fittings for Straight Sliding Timber Cabinet Doors

# **EKU Combino 60 H Infront**

- Application: Heavy-duty version of Combino 20/35 for general purpose top hung straight sliding inset cupboard doors of timber or metal construction
- Range: Max. door panel weight 60 kg Max. door height 2600 mm Max. door width 1400 mm For door thickness 19-27 mm, recommended door thickness 25 mm
- Trolley hangers: Top and back fixing; steel body with plastic tyred, ball bearing mounted wheels Back fixing version ± 3 mm adjustment using allen key, SW6
- Fittings: Supplied as individual items
- Important note: For extra robustness or where more than three panels on parallel tracks are used, continuous floor channels with guides are recommended (Details on request)

#### For ancillary door hardware i.e. locks, handles and bolts etc. refer to page 19

# A Top track

With screw holes, soffit fixing. Bright aluminium

Length	2.5 m	3.5 m
Cat. No.	405.69.025	405.69.035

Order qty: 1 pc (2.5 or 3.5 m length)

# **B** Double top track

With screw holes, soffit fixing. Bright aluminium

Length	2.5 m	3.5 m
Cat. No.	405.70.025	405.70.035

Order qty: 1 pc (2.5 or 3.5 m length)

#### C Fascia clip

Clips onto track A or B, every 700-800 mm. Predrilled for attaching wooden fascia. Bright aluminium

Cat. No. 405.70.090
---------------------

Order qty: 1 pc

# D Track stopper

For top track. Grey plastic with rubber buffer and galvanized steel spring retention catch

Order qty: 1 pc (order 2 pcs per length of single track or 4 pcs per length of double track)

#### **■** Trolley hanger, top fixing

Single roller. Suitable for metal doors. Galvanized steel body with plastic tyred, ball bearing mounted roller. No height adjustment

Cat. No. 405.76.320 Order qty: 1 pc (order 2 pcs per door)

### F Trolley hanger, back fixing

Single roller. Not suitable for metal doors. Height adjustable, ± 3 mm. Galvanized steel body with plastic tyred, ball bearing mounted roller

Cat. No.

405.76.350 Discontinued

Order qty:

405.76.350 use alt. no. 405.75.200

# G Rubber buffer

Screw fixing. Black rubber

407.01.930 Cat. No.

Order qty: 1 pc (order 2 pcs per door)

# H Rubber buffer. Plug-fit. Grey rubber

Cat. No. 406.24.101

Order qty: 1 pc (order 2 pcs per door)

## Lower guide profile

For glue mounting. Bright aluminium

Length	2.5 m	3.5 m
Cat. No.	405.04.250	405.04.350

Order qty: 1 pc (2.5 or 3.5 m length)

# J Bottom guide


Press-fit, spring loaded. Grey plastic

Cat. No. 405.04.040

Order qty: 1 pc




Top track surface mounted No groove in floor Lower profile groove mounted



(**©** 

() () ()




Drilling diagram for F

16 + 16 Α С D

Discontinued







- 27 16 16

<1111.

Item H.







31.08.10/2\*