

Timber treatment

Oil is required to treat the wood before use; the oil enhances the natural grain of the wood and gives it a water resistant seal.

Pure tung oil

- Conforms to BS EN71 Part 3
- Premium natural oil for wood care
- Ideal for use on food contact surfaces
- Highly resistant to water, alcohol and food acids
- For interior and exterior use
- Clear finish



Size	Cat. No.
250 ml	007.16.000
500 ml	007.16.001

Order qty: 1 pc

Finishing oil

- Conforms to BS EN71 Part 3
- Nourishes and enhances the natural colour of wood
- Provides a hard wearing and water resistant surface
- For use on furniture and turned woodwork
- For interior use only
- Clear finish



Size	Cat. No.
250 ml	007.16.030
500 ml	007.16.031

Order qty: 1 pc

Superior danish oil with UV filter

- Feeds, protects and enhances the natural colour of wood
- Use as an alternative to finishing oil on surfaces exposed to direct sunlight
- Apply with a brush or cloth
- Clear finish



Size	Cat. No.
250 ml	007.16.040
500 ml	007.16.041

Order qty: 1 pc

Oil brush

- Size 9
- Raw wood handle with red tip and brass ferrule, selected light China-bristles



Size	Cat. No.
30 mm	007.29.200
40 mm	007.29.201
50 mm	007.29.202
60 mm	007.29.203

Order qty: 1 pc

Cotton rags

- For making French polishing rubbers and as lint-free cloths for buffing wax polishes
- 100% pure cotton, white



Size	Cat. No.
500 g	007.54.510

Order qty: 1 pc



Routing jigs for timber worktops


- **Worktop jig, 720 mm:** Caters for 9 different worktop widths, incorporates both 50 and 100 mm radii
- **Worktop jig, 900 mm:** Cuts all popular size worktop widths including vanity unit, incorporates both 50 and 100 mm radii, plus 45° angle facility and 80 mm desk insert
- **Sink and hob aperture jig:** For routing apertures for sinks and hobs. Left and right hand radius curves at 100, 80, 60 and 40 mm, left and right hand 90° angles, straight edge 480 mm long
- **Belfast sink aperture jig:** For routing 530 x 430 mm aperture, to fit Belfast sink
- **Sloping drainer jig:** For routing sloping drainage grooves in a natural wood or stone worktop. Eliminates the need for measuring - just line up the jig on the worktop and clamp into place
- **Hot rod jig:** For routing grooves in a natural wood or stone worktop, to accommodate hotrods - hotrods protect the worktop from hot pans
- All jigs: Craft papers bound with phenolic resin and laminated with a melamine overlay. Fitting instructions included.



Jig carrying bag available separately for worktop jig 720 or 900 mm

Jig	Cat. No.	Jig carrying bag
Worktop jig, 720 mm	002.13.565	002.13.562
Worktop jig, 900 mm	002.13.566	002.13.563
Sink/hob aperture jig	002.21.500	
Belfast sink aperture jig	002.21.502	
Sloping drainer jig	002.21.501	
Hot rod jig	002.21.503	

Order qty: 1 pc



Worktop connecting bolt

- Comprises 1x bolt for installation in Ø 35 mm holes, 2x curved caps and 1x tightening nut
- Galvanized steel

Length	Cat. No.
65 mm	262.96.211
150 mm	262.96.220

Order qty: Multiples of 50 pcs



For routers please refer to Section 11 page 32