Glass Splashbacks and Upstands




A Glass splashbacks

- · Glass conforms to BS 62606 and PREN 12000
- · Self-adhesive backing for quick and easy installation
- 6 mm thick toughened glass
- 8 mm overall thickness including backing
- Hygienic and easy to clean
- · Glass is structurally very strong: combined with the adhesive backing and fixed to a plasterboard wall it takes a huge impact to break the glass. If the glass should break it will not shatter and will be held safely on the wall by the adhesive backing
- Can be fixed to any non-pourous, dry, dust and grease free surface e.g. Plastered walls, gyp board, tiles, MDF, chip board etc
- 2 mm gap should be left around all sides
- Must be sealed on all sides with a sanitary silicone sealant after installation to prevent dirt and moisture getting behind. If moisture does get behind the glass it will not effect the adhesive backing and will not be visible from the front face
- · Opaque coloured glass does not allow any show through of background
- · Lifetime guarantee on the colour will not degrade with heat or light
- · Toughened glass with polished edges

.83.170 .83.130	895 x 745 mm 564.83.172 564.83.132	995 x 745 mm 564.83.175 564.83.135
.83.130		
	564.83.132	564.83.135
00.000		
.83.230	564.83.232	564.83.235
.83.160	564.83.162	564.83.165
.83.260	564.83.262	564.83.265
.83.290	564.83.292	564.83.295
.83.100	564.83.102	564.83.105
.83.000	564.83.002	564.83.005
.83.040	564.83.042	564.83.045
.83.060	564.83.062	564.83.065
.83.070	564.83.072	564.83.075
	.83.230 .83.160 .83.260 .83.290 .83.100 .83.000 .83.040 .83.060 .83.070	.83.160 564.83.162 .83.260 564.83.262 .83.290 564.83.292 .83.100 564.83.102 .83.000 564.83.002 .83.040 564.83.042 .83.060 564.83.062

Order qty: 1 pc



IAFFI

B Glass splashbacks

- Glass conforms to EN 12600
- Pre-drilled for screw fixing to wall. Fixings included
- 6 mm thick toughened glass
- Hygienic and easy to clean
- Can be fixed to any non-pourous, dry, dust and grease free surface e.g. Plastered walls, gyp board, tiles, MDF, chip board etc
- 2 mm gap should be left around all sides
- Clear glass to allow background to show through
- · Toughened glass with polished edges

Finish	Width x I	Width x Height (+/- 2 mm tolerance)		
	595 x 745 mm	895 x 745 mm	995 x 745 mm	
Crystal	564.83.240	564.83.242	564.83.245	

Order qty: 1 pc

C Glass upstands

- Glass conforms to BS 62606 and PREN 12000
- Self-adhesive backing for quick and easy installation
- 6 mm thick float glass
- 8 mm overall thickness including backing
- · Hygienic and easy to clean
- · Glass is structurally very strong: combined with the adhesive backing and fixed to a plasterboard wall it takes a huge impact to break the glass. If the glass should break it will not shatter and will be held safely on the wall by the adhesive backing
- Can be fixed to any non-pourous, dry, dust and grease free surface e.g. Plastered walls, gyp board, tiles, MDF, chip board etc
- 2 mm gap should be left around all sides
- Must be sealed on all sides with a sanitary silicone sealant after installation to prevent dirt and moisture getting behind. If moisture does get behind the glass it will not effect the adhesive backing and will not be visible from the front face
- Opaque coloured glass does not allow any show through of background
- Lifetime guarantee on the colour will not degrade with heat or light
- Float glass with polished edges

Finish	Width x Height (+/- 3 mm tolerance)	
	995 x 140 mm	
Oyster white	564.83.673	
Linen	564.83.633	
Agate grey	564.83.733	
Silk grey	564.83.663	
Lilac	564.83.763	
China blue	564.83.793	
Olive	564.83.603	
Opal	564.83.503	
Ebony	564.83.543	
Aubergine	564.83.563	
Chalk	564.83.573	

Order qty: 1 pair