

## A Cleantec CTL Mini mobile dust extractor

- Electronic control for continuously variable suction force
- Integrated electric socket with automatic electronic on/off switch
- Compact design gives high mobility
- Space-saving storage for hose and cable
- Anti-static function prevents charging with static electricity
- For NON hazardous dusts
- · Systainer port on top of machine
- Supplied with:

2x Filter bags

Suction hose Ø 22 x 3.5 m-AS

Technical data	CTL Mini
Power consumption	400 - 1200W
Airflow max.	2800 l/min
Max. vacuum	20000 Pa
Filter surface	5000 cm <sup>2</sup>
Rubber-insulated mains	cable 7.5 m
Container/filter bag capa	acity 10/7.5 l
Dims. (L x W x H)	440x340x420 mm
Max. appliance socket connected load	
	2400 W
Weight	9.5 kg
Voltage	Cat. No.
240V	008.53.408
110V	008.53.428
Replacement parts	
Self clean filter bags	008.53.386*
0 1 1 1 11 1	

Order qty: 1 pc (1 set = 5 bags\*)



## B Cleantec CTL MIDI GB mobile dust extractor

- Electronic control for continuously variable suction force
- Integrated electric socket with automatic electronic on/off switch
- Compact design gives high mobility
- Space-saving storage for hose and cable
- Anti-static function prevents charging with static electricity
- For NON hazardous dusts
- · Systainer port on top of machine
- Supplied with:

2x Filter bags

Suction hose Ø 27 mm x 3.5 m-AS

Technical data	CTL MIDI GB	
Power consumption	400 - 1200W	
Airflow max.	2800 l/min	
Max. vacuum	20000 Pa	
Filter surface	5000 cm <sup>2</sup>	
Rubber-insulated mains cable 7.5 m		
Container/filter bag capac	ity 15/12.5 l	
Dims. (L x W x H)	440x340x470 mm	
Max. appliance socket connected load		
	2400 W	
Weight	9.7 kg	
Voltage	Cat. No.	
240V	008.53.391	
110V	008.53.392	
Replacement parts		
Filter bags	008.53.387*	
0 1 1 1 1 5 5 1		

Order qty: 1 pc (1 set = 5 bags\*)



## C CTL 26E GB mobile dust extractor

- Electronic control for continuously variable suction force
- Integrated electric socket with automatic electronic on/off switch
- · Compact design gives high mobility
- Space-saving storage for hose and cable
- Anti-static function prevents charging with static electricity
- For NON hazardous dusts
- · Systainer port on top of machine
- Supplied with:

1x Filter bag Suction hose Ø 27 mm x 3.5 m-AS Hose handle

Cable holder

Technical data	CTL 26E
Power consumption	350 - 1200 W
Airflow max.	3900 I/min
Max. vacuum	24000 Pa
Filter surface area	3060 cm <sup>2</sup>
Rubber-insulated mains cable 7.5 m	
Container/filter bag capa	acity 26/24 I
Dims. (L x W x H)	630x365x540 mm
Max. appliance socket connected load	
	2400 W
Weight	13 kg
Voltage	Cat. No.
240V	008.53.505
110V	008.53.504
Replacement parts	
Self clean filter bags	008.53.380*

Order qty: 1 pc (1 set = 5 bags\*)