



A Festool Cleantec CTM 26 E GB

- Approved for dust category M
- Antistatic function prevents static developing during work
- Constantly high suction because of the compact high performance turbine
- Attachment of Systainers via Sys-Dock
- Hose garage and cable wind up for the greater tidiness and safety
- Economical because of the optimal use of the available volume with a self clean filter bag in the container

• **Supplied with:**

- 1x Filter bag
- Suction hose Ø 27 mm x 3.5 m-AS
- Hose
- Cable holder

Technical data	CTM 26 E GB
Power consumption	350-1200 W
Airflow max.	3900 l/min
Max. vacuum	24000 Pa
Filter surface area	6318 cm ²
Rubber-insulated mains cable	7.5 m
Container/Filter bag capacity	26/24 l
Dims (L x W x H)	630x365x540 mm
Max. appliance socket connected load	2400 W
Weight	13.9 kg
Voltage	Cat. No.
240V	008.53.508

Order qty: 1 pc



B Festool Suction hose

- For use with CT dust extractors/SR suction units
- In accordance with DIN IEC 312
- Temperature resistant up to +70°C
- Leakage resistant in antistatic design (only guaranteed when used with a dust extractor with antistatic properties)
- With rotating adaptor and connection sleeve Ø 27 mm

Length	Cat. No.
3.5 m	008.56.110
5.0 m	008.56.111

Order qty: 1 pc



D Festool Plug it cable

- For use with all Festool power tools that have the 'plug it' feature
- Green PUR casing
- 4 m length

Voltage	Cat. No.
240V	000.07.930
110V	000.07.931

Order qty: 1 pc



C Festool Cleaning set

- For use with Festool dust extractor
- Consists of:
 - 4 pc full-length wand
 - 4 piece floor nozzle
 - crevice nozzle
 - upholstery nozzle
 - systainer case

	Cat. No.
Cleaning set	008.53.450

Order qty: 1 pc

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.