Festool Jigsaws



A Festool PS 300 EQ-PLUS jigsaw

- Patented three-way saw blade guide for cutting precise angles
- High-quality drive components give longer service life
- Improved splinterguard, no reworking
- Perfectly balanced for the effortless onehanded operation
- FastFix rapid-change system for easy saw blade changes
- Brilliant cutting power (MMC electronics)
- · Scope of delivery:

2x Saw blades Splinterguard

In a Systainer SYS 1 T-LOC

-	
Technical data	PS 300
Power consumption	720 W
Stroke rate	1000-2900 min-1
Pendulum cover adjustment in stages	
	4
Inclination	0-45°
Cutting depth in wood	120 mm
Cutting depth in NF metals	20 mm
Cutting depth in steel (soft)	10 mm
Weight	2.4 kg
Voltage	Cat. No.
240V	000.60.678

Order qty: 1 set

CH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.



B Splinter guard

• For use with jigsaws for splinter free cuts

, ,	•
	Cat. No.
Splinter guard	000.60.938

Order qty: Multiples of 20 pcs

HS 75/2,5 bir FESTOOL BIMETAL Lengths

Festool HS 75/2.5 biR reversed tooth jigsaw blade

- · Crossed teeth for fast cuts
- For softwood and hardwood, coated chipboard, veneered blockboard, soft plastics and acrylic Plexiglass®
- Max. material thickness 55 mm
- Tooth spacing 2.5 mm
- Toothed length 75 mm

	Cat. No.
HS 75/2.5 biR	000.70.819

Order qty: Multiples of 5 pcs

S 145/4 FSG FESTOOL TRION

Pestool S 145/4 FSG jigsaw blade

- · Crossed teeth for fast cuts
- For softwood and hard wood, untreated chipboard, coated chipboard and veneered plywood
- Max. material thickness 120 mm
- Tooth spacing 4 mm
- Toothed length 145 mm

	Cat. No.
S 145/4 FSG	000.70.741

Order qty: Multiples of 5 pcs

S 75/4 FESTOOL

E Festool S 75/4 jigsaw blade

- · Crossed teeth for fast cuts
- For softwood and hardwood, raw, veneered and laminated materials
- Max. material thickness 55 mm
- Tooth spacing 4 mm
- Toothed length 75 mm

	Cat. No.
S 75/4	000.70.753

Order qty: Multiples of 5 pcs

S 105/4 FSG FESTOOL TRION

F Festool S 105/4 FSG jigsaw blade

- · Crossed teeth for fast cuts
- For softwood and hardwood, raw, veneered and laminated materials
- Max. material thickness 85 mm
- Tooth spacing 4 mm
- Toothed length 105 mm

	Cat. No.
S 105/4 FSG	000.70.740

Order qty: Multiples of 5 pcs

S 75/4 FS FESTOOL TRION

G Festool S 75/4 FS jigsaw blade

- Clean cuts, tapered ground saw blade
- For softwood and hardwood, raw, veneered and laminated materials
- Max. material thickness 55 mm
- Tooth spacing 4 mm
- Toothed length 75 mm

	Cat. No.
S 75/4 FS	000.70.735

Order qty: Multiples of 5 pcs

S 75/4 K FESTOOL

H Festool S 75/4 K jigsaw blade

- · Crossed teeth for fast cuts
- For softwood and hardwood and soft plastics
- Max. material thickness 55 mm
- Tooth spacing 4 mm
- Toothed length 75 mm

	Cat. No.
S 75/4 K	000.70.762

Order qty: Multiples of 5 pcs



Festool S 75/2.5 jigsaw blade

- · Clean cuts, tapered ground saw blade
- For softwood and hardwood, raw, veneered and laminated materials, soft plastics, acrylic, Plexiglas®
- Tooth spacing 2 mm
- Toothed length 75 mm

	Cat. No.
S 75/2.5	000.70.726

Order qty: Multiples of 5 pcs



J Festool HS 60/2 bi jigsaw blade

- · Corrugated blade, machined teeth
- For non-ferrous metals, soft metals, aluminium, iron, sheet steel, steel profiles, stainless steel
- Max. material thickness 30 mm
- Tooth spacing 1.2 mm
- Toothed length 75 mm

	Cat. No.
HS 60/2 bi	000.60.185

Order qty: Multiples of 5 pcs



K Festool HS 105/1.2 jigsaw blade

- Resistant to high temperatures and wearing
- Corrugated blade, machined teeth
- For non-ferrous metals, soft metals, aluminium, sheet steel, steel profiles, sandwich materials/boards
- Max. material thickness 85 mm
- Tooth spacing 1.2 mm
- Toothed length 75 mm

	Cat. No.
HS 105/1.2	000.60.177

Order qty: Multiples of 5 pcs

Bosch equivalent jigsaw blades

Quick reference guide to replacement jigsaw blades shown on this page

, ,	3
Cat. No.	Bosch ref
000.70.741	-
000.70.753	T101DP
000.70.740	T101DP
000.70.735	T101DP
000.70.762	T244D
000.70.726	T101B
000.60.177	T318AF
000.60.185	T118BF

30.08.12