

A Festool Pendulum Carvex PS 420 **EBQ-PLUS** jigsaw

- Excellent behaviour in curves thanks to threefold saw blade guide and rigid lifter rod
- · Powerful cutting stroke for rapid working progress
- Simple handling thanks to the softgrip and ergonomic design
- Electronic switch on/off on both sides, reachable in every grip position
- Fast, tool-free changing of tables, baseplates and saw blades
- Low weight to save energy: 1.9 kg
- Easily visible scribe mark through stroboscope light and powerful extraction
- Tool length can be shortened with swivel-mounted plug it-cable

· Scope of delivery

2x Saw blades Splinterguard

In a Systainer SYS 1 T-LOC

Technical da	ta PS	420		
Stroke rate	1500-	1500-3800 min-1		
Pendulum cover adjustment in stages				
	4			
Cutting depth	oth in wood 120 mm			
Cutting depth in NF metals				
	20 mm			
Cutting depth in steel (soft)				
	10 mm			
Weight	1.9 kg			
Voltage	110V	240V		
Wattage	400W	550W		
Cat. No.	000.60.611	000.60.610		
0 1 1 1				

Order qty: 1 pc



B Festool Pendulum Carvex PSB 420 EBQ-PLUS jigsaw

- Excellent behaviour in curves thanks to threefold saw blade guide and rigid lifter rod
- · Powerful cutting stroke for rapid working progress
- Simple handling thanks to the softgrip and ergonomic design
- Electronic switch on/off on both sides, reachable in every grip position
- Fast, tool-free changing of tables, baseplates and saw blades
- Low weight to save energy: 1.9 kg
- Easily visible scribe mark through stroboscope light and powerful extraction

· Scope of delivery

2x Saw blades

Splinterguard

In a Systainer SYS 1 T-LOC

Technical da	a PSB 420			
Stroke rate	1000-	1000-3800 min-1		
Pendulum cover adjustment in stages				
	4			
Cutting depth	in wood 12	20 mm		
Cutting depth in NF metals				
	20	0 mm		
Cutting depth in steel (soft)				
	10 mm			
Weight	1.9 kg			
Voltage	110V	240V		
Wattage	400W	550W		
Cat. No.	000.60.613	000.60.612		

Order qty: 1 pc



C Festool Pendulum Carvex PSB 420 EBQ-SET jigsaw set

- Excellent behaviour in curves thanks to threefold saw blade guide and rigid lifter rod
- · Powerful cutting stroke for rapid working progress
- Simple handling thanks to the softgrip and ergonomic design
- Electronic switch on/off on both sides, reachable in every grip position
- Fast, tool-free changing of tables, baseplates and saw blades
- Low weight to save energy: 1.9 kg
- Easily visible scribe mark through stroboscope light and powerful extraction

· Scope of delivery

2x Saw blades

Splinterguard

Accessories Systainer

In a Systainer SYS 1 T-LOC

in a dystamor dro i i Lod				
Technical dat	ta PS	B 420		
Stroke rate	1000-	3800 min-1		
Pendulum cover adjustment in stages				
		4		
Cutting depth	in wood 12	20 mm		
Cutting depth in NF metals				
	20	0 mm		
Cutting depth	in steel (soft)			
	10 mm			
Weight	1.9 kg			
Voltage	110V	240V		
Wattage	400W	550W		
Cat. No.	000.60.615	000.60.614		
Order atu 1 no				

Order qty: 1 pc

Tools

Section 11 26R