Festool Belt Sanders and Accessories



- · Electronic control
- · Belt speed continuously variable for course and fine sanding
- Graphite sanding backing
- · Quick and easy belt tensioning and regulation
- · Sanding belts can be changed without any tools
- Supplied with: Systainer case, Stationary device for inversion, 4x sanding belts: P60, P80, P100, P120, Dust-extraction adapter and dust bag

Technical data	
Power consumption	1010 W
Belt width	75 mm
Belt length	533 mm
Sanding surface	135 x 75 mm
Belt speed, no load	200 - 380 m per minute
Belt speed, nominal load	150 - 320 m per minute
Connection for dust extraction	Ø 27/36 mm
Weight	3.8 kg
240V	+005.03.002

Order qty: 1 pc



B Sanding base

- For use with BS 75 E belt sander
- Replacement fabric and graphite base for general sanding work
- Cork and metal base for coarse sanding work

Material	Cat. No.
Cork/metal	+ 005.03.030
Fabric/graphite	+ 005.03.050

Order qty: 1 pc

C Flat frame

- For use with BS 75 E belt sander
- · With precision height adjustment and raising device for exact sanding of high quality surfaces

Item	Cat. No.
Flat frame	+ 005.03.040

Order qty: 1 pc

TCH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.

D Sanding belt, 533 x 75 mm

- For use with BS 75 E belt sander
- · For sanding wood

Gritt	Cat. No.
60	+005.03.206
80	+ 005.03.208
100	+005.03.210
120	+005.03.212
180	+005.03.218

Order qty: Multiples of 10 pcs



- · Ideal for large workpieces with wide sanding su
- Electronic control
- · Belt speed continuously variable for coarse and fine sanding
- Graphite sanding backing
- Quick and easy belt tensioning and regulation
- Sanding belts can be changed without any tools
- Supplied with: Systainer case, Stationary device for inversion, 4x sanding belts: P60, P80, P100, P120, Dust-extraction adapter and dust bag

Technical data	
Power consumption	1400 W
Belt width	105 mm
Belt length	620 mm
Sanding surface	160 x 105 mm
Belt speed, no load	230 - 380 m per minute
Belt speed, nominal load	170 - 340 m per minute
Connection for dust extraction	Ø 27/36 mm
Weight	6.5 kg
240V	+00 5.03.101

Order qty: 1 pc

F Sanding base

- For use with BS 105 E belt sander
- Replacement fabric and graphite base for general sanding work
- · Cork and metal base for coarse sanding work. Cork backed

Material	Cat. No.
Fabric/graphite/cork	005.03.120
Metal/cork	+ 005.03.140
Ouglass at set of the contains of algorithm	Do instated

Order qty: 1 pc (1 pc contains 2 sheets)

Item F.

G Flat frame

- For use with BS 105 E belt sander
- · With precision height adjustment and raising device for exact sanding of high quality surfaces

Item	Cat. No.
Flat frame	+ 005.03.130

Order qty: 1 pc

H Sanding belt, 620 x 105 mm

- For use with BS 105 E belt sander
- For sanding wood

Gritt	Cat. No.
60	+005.03.306
80	+ 005.03.308
100	+005.03.310
120	+005.03.312
180	+005.03.318

Order qty: Multiples of 10 pcs

11