Minifix K.D. Connecting Fittings


Minfix 15 Carbogloss Housings

- A Minifix 15 housings, without rim • For wood thicknesses from 15 or 16 mm
- Drive: Flat blade
- For connecting bolts with head Ø 6.5 and 7 mm, spreading bolts not suitable
- Polycarbonate

For wood	Dim.	Drilling depth		Cat. I	No.	
thickness from	Α	Х	White	Beige	Brown	Black
15 mm	7.5 mm	12.0 ^{+0.2} mm	262.15.707	262.15.412	262.15.109	262.15.305
16 mm	8.0 mm	12.5 ^{+0.2} mm	262.16.704	262.16.419	262.16.106	●2 62.16.302

Discontinued when stock

Order qty: Multiples of 100 pcs



ixconnect HAFE

B Minifix 15 housings, with rim

- For wood thicknesses from 15 or 16 mm
- Drive: Flat blade
- \bullet For connecting bolts with head Ø 6.5 and 7 mm, spreading bolts not suitable
- Polycarbonate

For wood	Dim.	Drilling depth		Cat.	No.	
thickness from	Α	Х	White	Beige	Brown	Black
15 mm	7.5 mm	12.0 ^{+0.2} mm	262.15.752	262.15.467	262.15.154	262.15.350
16 mm	8.0 mm	12.5 ^{+0.2} mm	262.16.759	262.16.464	262.16.151	262.16.357

Order qty: Multiples of 100 pcs



C Minifix 15 housings, without rim

- For wood thicknesses from 15 or 16 mm
- · Drive: Flat blade
- For connecting bolts with head \varnothing 6.5 and 7 mm, spreading bolts not suitable
- Polycarbonate

For wood	Dim.	Drilling depth	Cat. No.
thickness from	Α	X	Nickel coloured, tumble painted
15 mm	7.5 mm	12.0 ^{+0.2} mm	262.15.600
16 mm	8.0 mm	12.5 ^{+0.2} mm	262.16.600

Order qty: Multiples of 100 pcs



D Minifix 15 housings, with rim

- For wood thicknesses from 15 or 16 mm
- · Drive: Flat blade

CH-FF 2010, HUK. Dimensional data not binding. We reserve the right to alter specifications without notice.

- \bullet For connecting bolts with head Ø 6.5 and 7 mm, spreading bolts not suitable
- Polycarbonate

-			
For wood	Dim.	Drilling depth	Cat. No.
thickness from	Α	X	Nickel coloured, tumble painted
15 mm	7.5 mm	12.0 ^{+0.2} mm	262.15.650
16 mm	8.0 mm	12.5 ^{+0.2} mm	262.16.650

Order qty: Multiples of 100 pcs

