• EKU Combino U 50

- Application: For 1 or 2 overlay U-shaped sliding doors, which slide over the carcase and open at three sides. Concealed fittings and tracks. Ideal for custom-design room dividers or multimedia furniture
- Range: Max. door panel weight 50 kg
 For door thickness 19 mm
 Max. panel height 1200 mm*
 Max. panel width 1250 mm
 Max. panel depth (U shape) 700 mm
- *Note: For door heights more than 800 mm we recommend a door straightening fitting is used.
- Bottom track and centring set must be ordered separately
- Order adaptor separately if used in combination with EKU soft closing system; see pages 49-50

For ancillary door hardware i.e. locks, handles and bolts etc. refer to page 23

A Double bottom track

With screw holes, soffit fixing. Silver coloured anodised aluminium.

Length	2.5 m	3.5 m
Cat. No.	403.32.925	403.32.935

Order qty: 1 pc (2.5 or 3.5 m length)

EKU Combino U 50 fitting sets

- **B** Guide roller, for outer door. Excentric screw, allows ±2 mm depth adjustment. For recess mounting in carcase end panel. Grey plastic with roller.
- C Guide roller, for outer door. Sprung. For recess mounting in carcase end panel. Grey plastic with roller.
- Track stopper, for bottom track, with spring. Galvanized steel with rubber buffer and steel spring retention catch.
- **E Track stopper**, for bottom track, without spring. Galvanized steel with rubber buffer.
- Running gear, for inner door. Height adjustable +4/-2 mm. Galvanized steel body with plastic tyred, ball bearing mounted roller.
- **G Running gear**, for **outer** door. Height adjustable +4/-2 mm. Galvanized steel body with plastic tyred, ball bearing mounted roller.
- H Follower, for second door panel. White plastic.

_			
Fitti	ng sets for 1 do	or 2 doc	ors
В	Guide roller	1 pc	2 pcs
С	Guide roller, with sprin	g 1 pc	2 pcs
D	Stopper, with spring	2 pcs	4 pcs
E	Stopper, without sprin-	g 2 pcs	4 pcs
F	Running gear, inner do	or 4 pcs	4 pcs
G	Running gear, outer do	oor -	4 pcs
Н	Follower	-	2 pcs
Ca	at. No.	403.31.003	403.31.004

Order qty: 1 set

Sliding Door Fittings for Furniture


12

■ Centring set


For centring door panel, for version **without** mitre cuts. Anthracite plastic

Cat. No.	403.31.010

Order qty: 1 set



Top guide rollers recess mounted Bottom track surface mounted With screw fixing bottom rolling running gear



Compatible with EKU soft closing system shown on pages **60-61**

