## TCH 2013, @ Häfele U.K. Ltd 2013. Dimensional data not binding. We reserve the right to alter specifications without notice.

## **EKU Clipo 15GK Infront Door Fittings, No Drilling Required**

- Application: High quality straight sliding top hung door gear for 6 mm frameless glass panels for domestic or light-duty commercial
- Range: Maximum door weight 15 kg For glass thickness 6 mm
- Glass fixing profile at top of panel only no drilling required
- Tracks A and B are for min. 25 mm thick upper carcase
- Tracks C, D and E are for min. 19 mm thick upper carcase
- Top track C and double top track D are not suitable for hardwood





With concealed


fixing running






Е









To fasten upper tracks A/B, the upper carcase must be min. 25 mm thick





To fasten upper tracks C/D the upper carcase must be min. 19 mm thick. Not suitable for hardwood.







13.5






















## **EKU Clipo 15GK Infront tracks and channels**

Item	Description	Base material and finish	2.5 m	3.5 m
A Top track	with screw holes for soffit fixing into a groove	Bright aluminium	405.87.013	405.87.022
<b>B</b> Double top track (alternative)	with screw holes for soffit fixing into a groove	Bright aluminium	405.90.010	405.90.020
C Top track	with swivel lug soffit fixing at 100 mm intervals	Bright aluminium	405.86.016	405.86.025
<b>D</b> Double top track (alternative)	with swivel lug soffit fixing at 100 mm intervals	Bright aluminium	405.89.017	405.89.026
E Top track	with screw holes for surface soffit fixing	Anodised aluminium	405.81.010	405.81.020
H Frame profile	glue to glass	Silver anodised aluminium	405.78.925	405.78.935

## EKU Clipo 15GK Infront fitting sets and loose fittings

End dipo four filling sets and loose fittings					
Item	Description	Base material and finish	For 2 doors	Loose	
				fittings	
F Track stopper	for top tracks	Grey plastic	4 pcs	405.83.132	
<b>G</b> Running gear	slide in and screw fixing to profile <b>H</b> , ±1 mm vertical adjustment	Anthracite plastic	4 pcs	405.83.936	
I Rhodia 3B silicone	310 ml tube, for gluing glass to frame profile <b>H</b>	Clear	-	003.50.084	
<b>J</b> Guide	press-fit, for infront doors	Light grey plastic	2 pcs	405.83.122*	
Cat. No.			405.82.272		

Order 1 fitting set per pair of doors; for loose fittings order 2 pcs per door (order 1 pc per door\*) for Rhodia 3B silicone order 1 pc per pair of doors

Sliding Door Fittings for Furniture

12