

# Fittings for Straight Sliding Metal Interior Doors

## HAWA-Junior 120/M

- **Application:** Version of the Junior 120 system for top hung **metal** straight sliding doors. Vertically adjustable fitting for interior doors. All parts are corrosion resistant. Ideal for heavier duty cavity applications
- **Range:** Max. door weight **120 kg**  
Min. door thickness **35 mm**
- Installation drawing reference **14578**

### **A Junior 120 top track**

With screw holes for soffit fixing. Silver anodised aluminium.

**Two top tracks are mounted side by side for double or multiple doors**

Length	Cat. No.
2.5 m	941.20.250
3.0 m	941.20.300

Order qty: 1 length (2.5 or 3.0 m length)

### **B Trolley hanger**

Sleeve bearing mounted, high-grade polyamide, tandem rollers. Aluminium carriage.

**Order mounting plate C separately**

Cat. No.	941.20.012
----------	------------

Order qty: 1 pc (2 pcs required per panel)

### **C Mounting plate.** With M12 hanger bolt and fixing screws. Galvanized steel

Cat. No.	941.20.027
----------	------------

Order qty: 1 pc (2 pcs required per panel)

### **D Locking wrench.** For suspension assembly

Cat. No.	941.20.091
----------	------------

Order qty: 1 pc (1 pc required per application)

### **E Track stopper**

For adjustable mounting in top track. Zinc alloy housing with steel spring and rubber buffer. Adjustable retaining force.

**Important mounting note:** If the sliding door is required to stop at both ends, we recommend installing an additional track stopper

Cat. No.	941.20.041
----------	------------

Order qty: 1 pc (2 pcs required per panel)

### **F Rubber buffer.** Screw fixing

Cat. No.	940.40.051
----------	------------

Order qty: 1 pc (2 pcs required per panel)

**For clear threshold,** i.e. no floor channel, maximum door panel width 1 m, fix channel **G** to underside of door panel:

### **G Bottom guide channel**

20 x 20 mm. Pre-drilled for countersunk screws. Silver anodised aluminium

Length	Cat. No.
2.5 m	940.41.250
3.5 m	940.41.350

Order qty: 1 pc (2.5 or 3.0 m length)

### **H Guide**

For screw mounting to floor, clear threshold applications only. Grey plastic

Cat. No.	942.44.030
----------	------------

Order qty: 1 pc (1 pc required per panel)

**Heavier duty guiding;** use guide **I** with stainless steel floor channel **J**:

### **I Guide**

Stainless steel with brass roller

Cat. No.	930.10.000
----------	------------

Order qty: 1 pc (2 pcs required per panel)

### **J Floor channel**

Pre-drilled for countersunk screws. Stainless steel

Length	Cat. No.
2.1 m	943.26.921
2.5 m	943.26.925
3.0 m	943.26.930

Order qty: 1 pc (2.1, 2.5 or 3.0 m length)

