



- 3 section telescopic lift for compact installation height
- 5-100 kg maximum lift capacity
- 5-65 kg minimum and maximum lift capacity in standard installation
- 5-29 kg minimum and maximum lift capacity for lift mounted in the upside down position
- Input power: 110-240 VAC/ 50-60 Hz
- UK AC plug
- Remote controlled with RF and manual switch
- · Adjustable stroke
- · Automatic reverse function for improved safety
- Lid lifter and TV mounting brackets included
- Vesa fixing: 600 x 400, 600 x 200, 600 x 100, 400 x 400, 400 x 200, 400 x 100, 300 x 300, 200 x 200, 200 x 100
- Upside down use possible
- Black painted steel

Stroke	Cat. No.
1000 mm	421.68.423

Order qty: 1 pc

TCH 2013, © Häfele U.K. Ltd 2013. Dimensional data not binding. We reserve the right to alter specifications without notice.



Spare accessories



Spare remote RF system - Type A

- Basic RF remote system for items: 421.68.422/423 and 421.68.471
- Includes RF receiver/emitter and manual switch with switch mounting plate
- Black

	Cat. No.
Remote RF system - Type A	421.68.490

Order qty: 1 pc



Spare remote RF system - Type B

- For use with Plasma and LCD TV lift 421.68.380/470
- Black

	Cat. No.
Remote RF system - Type B	421.68.491

Order qty: 1 pc



Power supply, 220V

- For use with all lifts shown on pages 88 and 89
- Black

	Cat. No.
Power supply, 220V	421.68.492
0.1	

Order aty: 1 pc



Spare Remote control

• For use with all lifts shown on pages 88 and 89

0800 171 2909

• 55 x 39 x 12.5

	Cat. No.
Remote control	421.68.389

Order qty: 1 pc

PAGE AMENDED - 13.10.16/2