




Please order screws in multiples of order quantity shown

Spax screw, countersunk head



- > Fully threaded (*partially threaded)
- > Countersunk head with PZ cross slot
- > Yellox coated


Ø x Length/Thread	Driver required	Cat. No.	Order Qty
2.5 x 10 mm	PZ1	018.01.000	100
3.0 x 12 mm	PZ1	018.01.051	200
3.0 x 16 mm	PZ1	018.01.054	200
3.0 x 20 mm	PZ1	018.01.056	200
3.5 x 12 mm	PZ2	018.01.081	200
3.5 x 16 mm	PZ2	018.01.084	200
3.5 x 20 mm	PZ2	018.01.086	200
3.5 x 25 mm	PZ2	018.01.089	200
3.5 x 30 mm	PZ2	018.01.091	200
3.5 x 35 mm	PZ2	018.01.093	200
3.5 x 40 mm	PZ2	018.01.094	200
4.0 x 16 mm	PZ2	018.01.114	200
4.0 x 20 mm	PZ2	018.01.116	200
4.0 x 25 mm	PZ2	018.01.119	200
4.0 x 30 mm	PZ2	018.01.121	200
4.0 x 35 mm	PZ2	018.01.123	200
4.0 x 40 mm	PZ2	018.01.124	200
4.0 x 45 mm	PZ2	018.01.125	200
4.0 x 50 mm	PZ2	018.01.126	200
4.0 x 60 mm	PZ2	018.01.128	100
4.5 x 25 mm	PZ2	018.01.149	2000
5.0 x 25 mm	PZ2	018.01.179	200
5.0 x 30 mm	PZ2	018.01.181	200
5.0 x 40 mm	PZ2	018.01.184	200
5.0 x 45 mm	PZ2	018.01.185	200
5.0 x 50 mm	PZ2	018.01.186	200
5.0 x 60 mm	PZ2	018.01.188	100
5.0 x 70 mm	PZ2	018.01.190	100
5.0 x 80 mm	PZ2	018.01.191	100
5.0 x 90/60* mm	PZ2	018.01.492	100
5.0 x 100/60* mm	PZ2	018.01.493	100
6.0 x 60 mm	PZ3	018.01.218	100
6.0 x 80 mm	PZ3	018.01.221	100
6.0 x 100/60* mm	PZ3	018.01.523	100
6.0 x 120 mm	PZ3	018.01.525	100



> Screw drivers and driver bits are shown on pages **442-443**

> Imperial to metric screw size conversion chart shown on page **388**



Spax continuous hinge screw, countersunk head



- > Fully threaded
- > Countersunk head with PZ cross slot
- > Yellox coated

Ø x Length	Driver required	Cat. No.	Order Qty
3.0 x 12 mm	PZ1	018.42.501	100
3.0 x 16 mm	PZ1	018.42.502	100
3.0 x 20 mm	PZ1	018.42.503	100
3.0 x 25 mm	PZ1	018.42.504	100


Spax screw, collated, countersunk head



- > Strip feed
- > Fully threaded
- > Countersunk head with PZ cross slot
- > Zinc yellow passivated
- > Please note: Order quantities are per screw and not per strip
- > Compatible with auto feed machines from Makita, Senco, Hitachi, Durospin, Ryobi and Hilti

Ø x Length	Driver required	Cat. No.	Order Qty
4.0 x 35 mm	PZ2	018.41.501	500
4.0 x 40 mm	PZ2	018.41.502	500
4.0 x 45 mm	PZ2	018.41.503	500
4.0 x 50 mm	PZ2	018.41.504	500

Spax MDF screw, countersunk head



- > Countersunk head with T star
- > Wirox coated

Ø x Length	Driver required	Cat. No.	Order qty
3.5 x 40 mm	TS15	010.95.001	200
3.5 x 45 mm	TS15	010.95.002	200
3.5 x 50 mm	TS15	010.95.003	200
4.0 x 40 mm	TS20	010.95.004	200
4.0 x 45 mm	TS20	010.95.005	200
4.0 x 50 mm	TS20	010.95.006	200
4.0 x 60 mm	TS20	010.95.007	100