

2 hole security screw, countersunk

> Can only be removed with special bit, see item I shown on page 437

- > With 2 small holes drilled into the head
- > 304 stainless steel

Size	Driver size	Cat. No.	Order Qty
3.5 x 19 mm	TH4	010.93.001	100
3.5 x 25 mm	TH4	010.93.002	100
4.2 x 32 mm	TH5	010.93.003	100
4.2 x 38 mm	TH5	010.93.004	100
4.2 x 50 mm	TH5	010.93.005	100
4.8 x 38 mm	TH6	010.93.006	100
4.8 x 50 mm	TH6	010.93.007	100

Pin hex screw, countersunk

> Virtually impossible to remove without special bit, see item J shown on page 437

- > Hex socket with internal pin in the aperture
- > 304 stainless steel

Size	Driver size	Cat. No.	Order Qty
3.5 x 19 mm	H30	010.93.021	100
3.5 x 25 mm	H30	010.93.022	100
4.2 x 25 mm	H40	010.93.031	100
4.2 x 32 mm	H40	010.93.023	100
4.2 x 38 mm	H40	010.93.024	100
4.2 x 50 mm	H40	010.93.025	100
4.8 x 32 mm	H40	010.93.032	100
4.8 x 38 mm	H40	010.93.026	100
4.8 x 50 mm	H40	010.93.027	100
4.8 x 63 mm	H40	010.93.028	100

6-Lobe/Resistorex security screw, countersunk

> Requires special bit for installation and removal, see item K shown on page 437

- > Star drive with internal pin in the aperture
- > 304 stainless steel

Size	Driver size	Cat. No.	Order Qty
2.9 x 13 mm	T10	010.93.048	100
2.9 x 19 mm	T10	010.93.049	100
3.5 x 16 mm	T15	010.93.051	100
3.5 x 19 mm	T15	010.93.041	100
3.5 x 25 mm	T15	010.93.042	100
4.2 x 25 mm	T20	010.93.052	100
4.2 x 32 mm	T20	010.93.043	100
4.2 x 38 mm	T20	010.93.044	100
4.2 x 50 mm	T20	010.93.045	100
4.8 x 38 mm	T25	010.93.046	100
4.8 x 50 mm	T25	010.93.047	100

Sentinal one way pozi drive security screw

> Cannot be removed

- > For use with standard pozi or supadrive bits
- > Countersunk head twin thread wood screw
- > Mild steel

Size	Driver size	Cat. No.	Order Qty
3.5 x 25 mm	PZ2	010.93.062	200
4.2 x 19 mm	PZ2	010.93.068	200
4.2 x 32 mm	PZ2	010.93.063	200
4.2 x 38 mm	PZ2	010.93.064	200
4.8 x 38 mm	PZ2	010.93.066	200
4.8 x 50 mm	PZ2	010.93.067	200