

FIRE RATED SEALANTS

BI FR silicone sealant, fire retardant



- > Fire rated neutral cure silicone sealant for joints which require a highly elastic sealant (movement capacity of up to 50%)
- > Excellent adhesion to a wide range of building materials
- > Suitable for interior and exterior applications
- > Fire rating of up to 4 hours with normal backing material
- > Tested to BS476 part 20/22
- > 310 ml tube
- > Order qty: 1 pc

Colour	Cat. No.
White	003.50.020

Firecryl FR acrylic sealant, fire retardant



- > Water based acrylic sealant and crack filler
- > Paintable and remains flexible
- > Intumescent in a fire situation
- > Excellent adhesion to all porous surfaces
- > Suitable for interior joints with low or medium movement (movement capacity of up to 20%)
- > Fire rating of up to 4 hours with normal backing material
- > Tested to BS476 part 20/22
- > 310 ml tube
- > Order qty: 1 pc

Colour	Cat. No.
White	003.50.080

FS4 Fireshield Intumescent sealant



- > A high performance, flexible acrylic building sealant and adhesive
- > An indicative fire test based on BS476 Part 20 achieving a 4 hour fire rating
- > Manufactured to form an acoustic and fire rated intumescent barrier in construction applications
- > All surfaces to be sealed must be clean, dry and free from grease, laitance or dust that may hinder adhesion
- > 300 ml tube
- > Order qty: 1 pc

Colour	Cat. No.
White	003.50.260



- > Silicone cleaners, shown on page **494**
- > Guns and nozzles for use with these products, shown on page **477**