For optimum performance and +0.5 mm over the nominal runner thickness, for the runner space.


Installed length


No

19.3

-20.5

_(φ)







46.5





- > For interlock both sides order: 2x Interlock runners 422.45.02X
- > For interlock one side order: 1x Interlock runner 422.45.02X 1x Companion slide 422.45.03X
- > Locking kit 237.54.300 must be ordered separately, shown on page 217
- > Interlock slide (anti-tilt) with locking option
- > Load carrying capacity up to 100 kg (see below for individual runner capacity)
- > Hold-in feature holds the drawer in
- > Suitable for drawers up to 1000 mm wide (for drawers 800-1000 mm wide the use of 2x interlock runners is recommended)

Travel length ±3

- > Zinc-plated steel
- > Kit consists of:
 - 1x Interlock slide
 - $1x \varnothing 6 \times 300$ mm rod. Cut to suit required pitch
- > Order fixing screws separately
- > Order qty: 1 kit

Full Extensio

			CICLES	©6 Ø 4.0
Installed length	Travel length	Load capacity	Load capacity	Cat. No.
		(up to 800 mm wide drawers)	(up to 1000 mm wide drawers)	
350 mm	355 mm	85 kg	75 kg	422.45.021
400 mm	430 mm	90 kg	80 kg	422.45.022
450 mm	480 mm	95 kg	85 kg	422.45.023
500 mm	530 mm	100 kg	90 kg	422.45.024
550 mm	580 mm	95 kg	85 kg	422.45.025
600 mm	630 mm	85 kg	75 kg	422.45.026
650 mm	680 mm	80 kg	70 kg	422.45.027
700 mm	730 mm	70 kg	60 kg	422.45.028