
# HÄFELE 110° CAM OR STANDARD ADJUSTMENT HINGE



#### Drilling pattern for cup fixing





Soft close clip on fitting for sprung hinges shown on page **328** 


- > Opening angle 110°, Ø 35 mm cup
- > Screw fixing cup
- > Click on or slide on arm
- > For door thickness up to 22 mm see table below
- > Full overlay mounting steel cup and hinge arm, half overlay and inset mounting steel cup and zinc alloy arm
- > Available with cam or standard depth adjustment
- > Order fixing screws separately
- > Order qty: 1 pc

#### Häfele 110° hinge

Minimum gap for doors with chamfered edges (r = 1 mm) with factory setting

Door thickness	Distanc	Distance to cup E mm				
mm	3.0	4.0	5.0			
16	0.3	0.3	0.3			
17	0.5	0.5	0.5			
18	0.7	0.7	0.7			
19	1.0	0.9	0.9			
20	1.3	1.2	1.2			
21	1.7	1.6	1.5			
22	2.5	2.1	2.0			
	Minimum gap F					

# Full overlay mounting, cam adjustment




Door over	day mm						
	13	14	15	16	17	18	
				3	4	5	0
	3	4	5				3
Distance to cup E mm			Мог	ınting pla	ate heig	ht mm	
JISTAI ICE	to cup L	_ 1111111		IVIOC	iritirig pia	ate Helg	1





Fixing Click on Screw fixing 312.29.500

## Half overlay mounting, cam adjustment



Door ove	erlay mm						
	4	5	6	7	8	9	
				3	4	5	0
	3	4	5				3
D:-1		_			and the second		

Distance to cup E mm

Mounting plate height mm



Type	Click on
Cat. No.	312.29.501



## Full overlay mounting, standard adjustment




Door ove	erlay mm						
	13	14	15	16	17	18	
				3	4	5	0
	3	4	5				3
Distance	Distance to cup E mm			Мос	ınting pla	ate heig	ıht mm





Fixing	Click on	Slide on
Screw fixing	312.20.550	312.00.550

## Half overlay mounting, standard adjustment




Door ove	erlay mm						
	4	5	6	7	8	9	
				3	4	5	0
	3	4	5				3
Distance	Distance to cup E mm			Мос	unting pla	ate heig	ıht mm





lype	Click on	Slide on
Cat. No.	312.20.551	312.00.551

#### Inset mounting, standard adjustment



Door thi	ckness m	ım					
	16	17	18	19	20	21	
	3	3	3				2
	4/5	4	4	3	3	3	3
Distance to cup E mm				G	ap F m	ım	

Dimensions given are using a 3 mm mounting plate





Type	Click on	Slide on
Cat. No.	312.20.552	312.00.552

YOU ALSO NEED: 🗸





OPTIONAL ACCESSORIES Pages 328, 403-417

#### Mounting plate for Häfele concealed hinges









Click on

DRAWER SYSTEMS, STAYS AND HINGES 2015, © Hätele U.K. Ltd 2015. Dimensional data not binding. We reserve the right to alter specifications without notice.

Slide on



- > Hospa screw fixing
- > One part plate with  $\pm$  2 mm height adjustment via slots
- > Nickel-plated steel
- > Order fixing screws separately
- > Order qty: 1 pc



**BEST** 

Height	Click on	Slide on
0 mm	312.30.540	312.10.560