


TIOMOS 95° MINI HINGE

NEW


Drilling template 45/9.5
For screw fixing

- > Hinge for small doors and doors with narrow frames
- > Opening angle 95°
- > Ø 26 mm cup
- > For door thickness up to 24 mm (for door thicknesses 24 mm and above, a trial fitting is recommended)
- > Flat hinge arm
- > Available with or without self-closing mechanism (spring)
- > Click on arm
- > 3-dimensional adjustment with appropriate mounting plate
- > Without integrated damper
- > Order fixing screws separately
- > Order qty: 1 pc

Tiomos 95° mini

Door thickness mm	Distance to cup E mm			
	3.0	4.0	5.0	6.0
16	1.0	1.0	1.0	1.0
18	1.5	1.5	1.6	1.7
20	2.3	2.5	2.9	3.4
22	3.7	4.1	4.6	4.2
Minimum gap F				

TIOMOS 95° Mini hinge



Door overlay mm

13	14	15	16	17	18	
		3	4	5	6	0
3	4	5	6	7		2

Distance to cup E mm

Mounting plate height mm



Soft close

With spring

Without spring

Without

348.25.500

348.25.300



YOU ALSO NEED:


MOUNTING PLATES
Pages 364-366

FIXING SCREWS
Page 468

OPTIONAL ACCESSORIES
Pages 367-368, 403-417

Cruciform mounting plate, 4 point fixing


A wider range of mounting plates are shown
on pages **364-366**

- > For TIOMOS click on fixing hinges only
- > Hospa screw fixing
- > Two part plate with ± 2 mm height adjustment via worm screw
- > Nickel-plated steel
- > Order fixing screws separately
- > Order qty: 1 pc

BEST
SELLER

Height

Hospa screw

0 mm

348.38.511