

# HÄFELE 110° SMUSO QUICK FIXING SOFT CLOSE HINGES



- > Opening angle 110°
- > Full overlay, half overlay/twin or inset mounting
- > Automatic closing
- > Ø 35 mm cup
- > For door thickness 14-22 mm see table below
- > Screw fixing cup
- > Smuso quick fixing arms
- > Choice of drilling patterns 45/9.5 or 48/6
- > Integrated soft close
- > Nickel-plated pressed steel cup and arm
- > Order fixing screws separately for screw fixing versions
- > Order qty: Multiples of 50 pcs








Smuso - with integrated soft closing mechanism


## Full overlay mounting



Over	lay - co	overage	of the s	ide end	by door	e mm		
12	13	14	15	16	17	18	19	
				3	4	5	6	0
		3	4	5	6			2
3	4	5	6					4

DBE distance to cup bore edge mm Mounting plate height f mm








Drilling pattern	45/9.5	48/6
Screw fixing	311.60.505	311.60.525

PAGE AMENDED **02.11.16/1** 



## Half overlay/twin mounting



Over	lay - cc	verage	of the s	ide end k	oy door	e mm		
5	6	7	8	9	10	11	12	
				3	4	5	6	0
		3	4	5	6			2
3	4	5	6					4
DBE distance to cup bore edge mm				Mou	Mounting plate height f mm			


smuso)

FIXINGS REQUIRED HOSPA Ø 3.5

 Drilling pattern
 45/9.5
 48/6


 Screw fixing
 311.60.506
 311.60.526

## Inset mounting



Overlay - coverage of the	side end	by door	e mm		
	-3	-3	-1	0	
	6	5	4	3	0
			5	6	2

DBE distance to cup bore edge mm Mounting plate height f mm



FIXINGS REQUIRED HOSPA Ø 3.5

 Drilling pattern
 45/9.5
 48/6

 Screw fixing
 311.60.507
 311.60.527

YOU ALSO NEED:





OPTIONAL ACCESSORIES
Pages 403-417

### Super compact cruciform mounting plate



- > For Smuso quick fixing systems
- > Hospa screw fixing
- > Two part plate with ± 2 mm height adjustment
- > Nickel-plated steel
- > Order fixing screws separately
- > Order qty: Multiples of 10 pcs



FIXINGS REQUIRED HOSPA Ø 3.5

BEST

SELLER

Height Hospa screw 0 mm 311.71.570



A wider range of mounting plates are shown on page **402**