

Rigid pipe



- > Recommended component for maximum airflow
- > Flame retardant white PVC
- > Order qty: 1 pc (1 pc = 1 m length)

System	Cat. No.
System 4	565.30.800
System 5	565.30.802
System 6	565.30.804

Connector



System 5



Systems 4 and 6

- > White flame retardant material
- > To be used with rigid pipe 565.30.800/2/4
- > Order qty: 1 pc

System	Cat. No.
System 4	565.30.600
System 5	565.30.900
System 6	565.30.602

Round reducer



These may be used as fan connectors, but may reduce airflow

- > Choice of three sizes:
System 5, suitable for many applications where a system 5 spigot or flange needs to be connected to a system 4 component
Suitable where approx. Ø 150 mm spigot needs to be connected to a system 5 component
Suitable where approx. Ø 125 mm spigot needs to be connected to a system 6 component
- > Flame retardant white material
- > Order qty: 1 pc

System	Cat. No.
System 5 to 4	565.30.860
System 6 to 5	565.30.861

90° Round pipe connector



- > Flame retardant white material
- > Order qty: 1 pc

System	Cat. No.
System 4	565.30.825
System 5	565.30.826
System 6	565.30.821



- > System **4** = aprox Ø 100 mm (internal dimension)
- > System **5** = aprox Ø 120 mm (internal dimension)
- > System **6** = aprox Ø 150 mm (internal dimension)