

LOOX 24V LED 3010 DOWNLIGHT

Recessed or with two options for surface mounting, this 3.25W light provides excellent output




24V SYSTEM

Loox 24V LED 3010 downlight, Ø 65 mm



Choice of clear or frosted glass cover included



- > For recess mounting, press-fit in Ø 60 mm hole
- > Voltage: 24V. Wattage: 3.25W
- > With 2.0 m lead with Loox 24V connector
- > Silver coloured anodised aluminium with clear glass cover, optional replacement frosted glass cover also included
- > Order qty: 1 pc

Distance	105°	3200 K	4000 K	6500 K
250 mm		1240 Lx	1325 Lx	1350 Lx
500 mm		310 Lx	331 Lx	338 Lx
750 mm		138 Lx	147 Lx	150 Lx
1000 mm		78 Lx	83 Lx	84 Lx



Order bezels or rectangular housing separately for surface mounting, shown on page **109**

Output:	3200 K	4000 K	6500 K
Light colour:	Warm white	Cool white	Daylight white
Wattage (W):	3.25	3.25	3.25
Energy efficiency:	A+	A+	A+
Number of diodes:	1	1	1
Light output (Lm):	250	267	271
Efficacy (Lm/W):	77	82	83
Colour Rendering Index:	82	84	83



Finish	3200 K	4000 K	6500 K
Silver coloured	833.75.040	833.75.041	833.75.042

YOU ALSO NEED:



DRIVER
Page 126



SWITCH
Pages 128-131

OPTIONAL ACCESSORIES
Pages 127, 133-135