


LOOX 12V LED 2020 DOWNLIGHT

This light is suitable for use in wet areas (zone 1) of bathrooms or kitchens when recess mounted. It also has an opaque cover which provides an even distribution of light.



12V SYSTEM

Loox 12V LED 2020 downlight, Ø 65 mm, IP44 rated



- > For recess mounting, press-fit in Ø 55 mm hole
- > Voltage: 12V. Wattage: 2.7W
- > With 2.0 m lead with Loox 12V connector
- > Zinc alloy housing with opaque lamp cover
- > Order qty: 1 pc

Output:	3000 K	4000 K	5000 K
Light colour:	Warm white	Cool white	Daylight white
Wattage (W):	3.2	3.2	3.2
Energy efficiency:	A	A	A
Number of diodes:	6	6	6
Light output (Lm):	134	142	140
Efficacy (Lm/W):	50	53	52
Colour Rendering Index:	84	85	88

Distance	103°	3000 K	4000 K	5000 K
250 mm		766 Lx	848 Lx	848 Lx
500 mm		210 Lx	220 Lx	215 Lx
750 mm		85 Lx	94 Lx	94 Lx
1000 mm		48 Lx	53 Lx	53 Lx

833.72.020
replaced by 833.72.280
833.72.030
replaced by 833.72.282
833.72.021
replaced by 833.72.283
833.72.031
replaced by 833.72.285
833.72.022
replaced by 833.72.286
833.72.032
replaced by 833.72.288



Order bezel separately for surface mounting



Finish	3000 K	4000 K	5000 K
Matt nickel	833.72.280	833.72.283	833.72.286
Polished chrome	833.72.282	833.72.285	833.72.288


YOU ALSO NEED:

DRIVER
Page 90

SWITCH
Pages 92-95

OPTIONAL ACCESSORIES
Pages 91, 97-99

Loox 12V LED 2020 bezel, Ø 66.5 mm



- > For surface mounting Loox LED 2020 downlight
- > Screw fixing
- > Zinc alloy
- > Order qty: 1 pc



Note: IP rating is 20 when light is surface mounted



Finish	Cat. No.
Nickel silver coloured	833.72.800
Polished chrome	833.72.802

PAGE AMENDED
14.10.16/3