
## THRESHOLD AND WEATHER SEALS

Threshold and weather protection for a wide range of applications of sliding and hinged doors.

## Retractable door seal, full mortice




- > Regular duty
- > For timber or metal doors
- > Unhanded
- > For seal gap up to 12.7 mm
- > May be trimmed on site by 152 mm to fit
- > Aluminium carrier with solid neoprene seal
- > Order qty: 1 pc

Length	914 mm	1067 mm
Cat. No.	950.07.544	950.07.546

## Hawa Sealing and buffer profile



- The door requires two grooves to accommodate the profile.
  - The bulge of the profile is determined by the interval between the gaps




- > Installed in two grooves in the front edge of sliding doors,
- Profile strip absorbs impact noise and prevents possible finger injury from forceful closing
- > Seals the door when closed
- > Neoprene
- > Order qty: 1 roll (= 5 m lengths)



Finish	Brown	Black
Cat. No.	940.00.521	940.00.530

## Slide-pile weather strip



- > Suitable for both hinged and sliding doors, windows
- > Inward or outward opening
- > Suitability: Residential, commercial and public, industrial and normal site conditions
- > Resilient polypropylene pile in aluminium carrier
- > Stainless steel pin fixing included
- > Aluminium carrier, polypropylene pile seal
- > Order qty: 1 pc



Length	Cat. No.
2134 mm	950.17.270