

METAL VISION FRAMES

Porthole frames and glass.

2

Door Accessories: Seals



Circular vision panel, non fire rated



- > To suit maximum door thickness 44 mm
- > Ø 250 mm set consists of:
 - 1x 973.99.000 Frame, Ø 200 mm (for Ø 250 mm door cut size)
 - 1x 973.99.200 Clear laminated glass, Ø 223 mm, 6.4 mm thick
 - 1x 973.99.110 Glazing tape, 1.6 mm thick, 2.4 m length
- > Ø 350 mm set consists of:
 - 1x 973.99.010 Frame, Ø 300 mm (for Ø 350 mm door cut size)
 - 1x 973.99.210 Clear laminated glass, Ø 323 mm, 6.4 mm thick
 - 1x 973.99.110 Glazing tape, 1.6 mm thick, 2.4 m length
- > Order qty: 1 set

COMPLIES
WITH
BS 476
PART 22

TESTED IN
ACCORDANCE
WITH
BS EN
1634-1

Fixings
included
✓

Frame finish	Ø 250 mm	Ø 350 mm
Satin stainless steel	973.99.300	973.99.302

Ø 250 mm Circular vision panel, 30 min. fire rated



- > To suit maximum door thickness 44 mm
- > Ø 250 mm set consists of:
 - 1x 973.99.000 Frame, Ø 200 mm (for Ø 250 mm door cut size)
 - 1x 973.99.203 Clear glass FD 30, Ø 223 mm, 6 mm thick
 - 1x 973.99.110 Glazing tape, 1.6 mm thick, 2.4 m length
 - 1x 973.99.120 Intumescent liner FD30, 1.6 mm thick, 2.4 m length
- > Ø 350 mm set consists of:
 - 1x 973.99.010 Frame, Ø 300 mm (for Ø 350 mm door cut size)
 - 1x 973.99.213 Clear glass FD 30, Ø 323 mm, 6 mm thick
 - 1x 973.99.110 Glazing tape, 1.6 mm thick, 2.4 m length
 - 1x 973.99.120 Intumescent liner FD30, 1.6 mm thick, 2.4 m length
- > Order qty: 1 set

Fire rated
30
minute

COMPLIES
WITH
BS 476
PART 22

TESTED IN
ACCORDANCE
WITH
BS EN
1634-1

Fixings
included
✓

Frame finish	Ø 250 mm	Ø 350 mm
Satin stainless steel	973.99.301	973.99.303

TCH AH 2016, © Häfele U.K. Ltd 2016. Dimensional data not binding. We reserve the right to alter specifications without notice.