

## Stainless steel, shrouded bearing, lift off hinge, 102 x 102 mm





Clockwise closing =

Left hand hinge

Anti-clockwise closing =

Right hand hinge



- > Staggered hole pattern
- > Maximum adjusted door weight 80 kg
- > Minimum door thickness 44 mm
- > Square and radius corners
- > Maintenance free
- > Grade 304 stainless steel




Finish	Satin	Polished
Square corners		
Clockwise closing	926.91.560	926.91.561
Anti-clockwise closing	926.91.562	926.91.563
Radius corners		
Clockwise closing	926.91.570	926.91.571
Anti-clockwise closing	926.91.572	926.91.573

## Phoenix Mild steel, fixed pin, 3 knuckle, shrouded bearing butt hinge, 102 x 76 mm



- > Maximum adjusted door weight 100 kg
- > Minimum door thickness 44 mm
- > Maintenance free
- > 3 knuckle hinge with fixed pin and shrouded bearings
- > Ø 5 x 30 mm wood screws included
- > Approved CF 351 certifiere
- > Mild steel
- > Order qty: 1 pc



BS EN 1935

4 7 5 1 1 0 0 12



Finish	Cat. No.
Polished chrome	926.91.462
Satin nickel	926.91.466
Zinc-plated	926.91.469



Copper finishes are also available to order on request - please contact us for further information