
Startec single push bar panic latch









- > Designed to satisfy the requirements of a panic application: Fire rated for timber and steel doors
 - Suitable for single doors and the active leaf (1st opening) of a rebated double door set
- > 180 x 55 x 98 mm (height x width x depth, excluding bar)
- > Suitable for doors up to 1300 mm wide
- > Universal non-handed
- > Low projection, category 1 the hardware stands off the door no more than 100 mm - allowing the hardware to be used on any fire or escape door that will not open beyond 90°
- > Can be used with accessories rim cylinder, digital codelock, or outside access device
- > Supplied with universal cast striker
- > The keep can be surface mounted or morticed into the frame for a single door
- > Order qty: 1 set











Fixings


Finish Silver powder coated Left hand


Right hand 911.53.199

911.53.198

Startec single push bar panic bolt







- > Designed to satisfy the requirements of a panic application: Fire rated for timber and steel doors Suitable for single doors and the inactive leaf (2nd opening) of a rebated double door set
- > 180 x 55 x 98 mm (height x width x depth, excluding bar)
- > Suitable for doors up to 1300 mm wide and 2500 mm high
- > Unhanded
- > Low projection, category 1 the hardware stands off the door no more than 100 mm - allowing the hardware to be used on any fire or escape door that will not open beyond 90°
- > Can be used with an outside access device
- > Supplied with an easy clean socket, horizontal bar and vertical bolts which can be cut on site. For single doors providing two point locking or on the inactive leaf of a rebated set of double doors or on a pair of non-rebated double doors
- > Includes an anti-thrust device to prevent the shoot bolt from being retracted
- > Adjustable top and bottom shoot bolts, offering +/- 5 mm adjustment
- > Order qty: 1 set



BS EN









Finish

Unhanded Silver powder coated 911.53.012



- > Outside access devices are shown on page 198
- > Suitable digital lock is shown on page 197

specifications without We reserve the right to alter 2016, © Häfele U.K. Ltd 2016. Dimensional data not binding. TCH AH