## HXFELE

## Touch bar deadlocking latch





- > For single outward opening doors max. 1220 mm wide
- > Used in conjunction with 2 point locking (see page 260) and a catch touchbar unit
- > Anti-thrust latch bolt
- > Suits either hand
- > Exit only
- > Fixings included, for timber doors
- > Self adhesive vinyl 'Push bar to open' sign included
- > Main body and touch bar, rolled steel. Internal components are zinc-plated steel and diecast aluminium. Silver epoxy powder coated or satin stainless steel plated finish
- > We are able to supply this product with built-in alarm, built-in micro-switches and other finishes to order, subject to quantity
- > Can be used with an outside access device
- > Order qty: 1 set




## Touch bar mortice latch actuator

64 55

0





- > For single outward opening doors max. 1220 mm wide
- > Anti-thrust latch bolt
- > Suits either hand
- > Exit only
- > Self adhesive vinyl 'Push bar to open' sign included
- > Main body and touch bar, rolled steel. Internal components are zinc-plated steel and diecast aluminium. Silve epoxy powder coated or satin stainless steel plated finish
- > We are able to supply this product with built-in alarm, built-in micro-switches and other finishes to order, subject to quantity
- > Also available without lock case. Note that these do not conform to CEN standards
- > If required to open externally order cylinders separately
- > Order qty: 1 set





We strongly recommend the use of hinge bolts or security hinges with panic hardware



- > Outside access devices are shown on page 206
- > Cylinders are shown on pages 65-77
- > Signage associated with panic exit devices, i.e. 'Push bar to open' and 'Fire escape keep clear' see Section 2 pages 134-142