

HAWA-JUNIOR 120/GP WITH FIXED GLASS PANEL


For wherever rooms need closing with unobtrusive, reliable all glass sliding doors at optimum price/performance, e.g. in hotels, restaurants, conference rooms, airports, office buildings or private residential interior and outdoor applications.


- > HAWA-Junior 120/GP with fixed glass
- > Fixed glass panel is positioned into retainer part of top track A shown below. No glass cut outs or additional hardware required
- > Retainer profile for wall and floor fitting provides sufficient stability.
- > Rubber profile or silicone groove holds the glass in position and prevents humidity seeping between glass and track
- > Easy fitting of fixed glass panel:
 - 1. Slide glass into retainer part of top track A
 - 2. Position the glass on the spacing block in the bottom profile C and/or
 - 3. Slide sideways into wall profile C
 - 4.Clip cover profile B into retainer part of top track A for walk-through area 5 Seal fixed class with either rubber profile D or silicone provided by
 - 5.Seal fixed glass with either rubber profile D or silicone provided by customer












HAWA-Junior 120/GP



HAWA-Junior 120/GP tracks and fitting sets must be ordered separately, shown on pages 122-123

Top track and cover profile for fixed glass panel




- > A Top track
- > With integrated retainer for fixed glass, with screwholes
- > Silver anodised aluminium
- > Order qty: 1 pc
- > B Cover profile
- > For use with fixed glass top track A, clips into and closes retainer in walk-through area, silver anodised aluminium
- > Order qty: 1 pc

1
306
n
132




Bottom/wall profiles and glass retainer



- > C Bottom/wall profile, with screw holes, silver anodised aluminium
- > Order qty: 1 pc
- > D Rubber profile, black
- > Order qty: 1 roll
- > E Bottom/wall glass retainer, with screw holes and rubber profile, silver anodised aluminium, 50 mm
- > Order qty: 1 pc

Bottom/wall profile	3.5 m
Item C	940.41.535
Rubber profile	10 m
Item D	940.41.053
Bottom/wall glass retainer	Silver anodised
Item E	940.41.054


Centring door stop, with wall profile and rubber seal



- > F Wall profile, undrilled, silver anodised aluminium
- > Order qty: 1 pc
- > G Rubber seal, for use with profile F, black rubber
- > Order qty: 1 pc
- > H Centring door stop, for insertion into wall profile F, black plastic
- > Order qty: 1 pc

Wall profile	2.5 m	3.5 m
Item F	941.24.925	941.24.935
Rubber seal	2.5 m	3.5 m
Item G	941.24.081	941.24.082
Centring door stop		
Item H		941.24.043

Alternative centring door stop



TCH AH 2016, @ Häfele U.K. Ltd 2016. Dimensional data not binding. We reserve the right to alter specifications without notice.

- > Wall fixing
- > Grey plastic
- > Order qty: 1 pc (2 pcs required per panel)

	Cat. No.
Centring door stop	941.24.042

Rubber profile



- - Longer lengths of rubber profile and transparent version also available on request

- > For vertical glass edge protection recommended for glass doors that can strike against one another
- > Self adhesive, black
- > Order qty: 1 roll

Length	5.0 m
For 8/10 mm glass thickness	404.95.321