


FOLDASIDE 240 ENDFOLD FOLDING DOOR SYSTEM

Top hung internal end folding partitions, timber or metal doors. For residential and light commercial applications.
No rebated head facility.

- > Foldaside 240 Endfold
- > Range:
 - Max. door weight **36 kg**
 - Max. door height **2.4 m**
 - Max. door leaf width **800 mm**
 - For door thickness **35 to 44 mm**
- > When swing leaves hinged to folding suites reduce door leaf widths to 700 mm and use 4 wheel hangers adjoining swing leaf
- > Up to 8 leaves may be hinged together
- > Loose or floating suites of door leaves are not recommended
- > Track brackets usually soffit fixed, additional brackets required where doors stack
- > All hangers have vertical adjustment
- > Floor channel unnecessary under swing leaves




Series 200 System top track brackets - Selection Guide


- 1 - Closed end brackets should be fitted at **both ends** of each track run
- 2 - Lock joint brackets should be fitted at each **track joint**
- 3 - Brackets should be positioned at 600-900 mm centre intervals along the track

Examples

2 m length of track



3 m length of track



2 x 3 m lengths of track



Key
O = Open bracket
C = Closed end bracket
L = Lock joint bracket

- !** > This is a guide only. If very heavy or large numbers of panels are proposed, additional brackets may be required - Please contact us for further assistance

Important:

Where the jamb to first leaf joint is hinged with butt hinges, the first leaf must be narrower in width than the other leaves in the suite. The dimension is **A** or **B** shown below



A = 1/2 door thickness + 29 mm + 1/2 hinge knuckle diameter + X, **X** = Rebate depth

B = 1/2 door thickness + 29 mm + 1/2 hinge knuckle diameter



Example:

To find **B**, where door = **44 mm thick** and hinge knuckle diameter = **12 mm**

B = 22 + 29 + 6 = **57 mm**




- ➔** > Hinges and accessories must be ordered separately, shown on pages **162-163**




3, 5 or 7 leaves one way incorporating access door

4 wheel hanger
 Flush handle with roller catch or flush ring handles with mortice lock



Foldaside 240 Endfold tracks and fixing brackets




! > Refer to top track brackets selection guide shown on page 166

- > A Top track, galvanized steel (1.6 mm gauge) to BS EN 10142
- > B Side fixing bracket, open, 92 x 50 mm, for closed end piece use item E, galvanized pressed steel
- > C Lock joint plate, 83 mm, to convert to lock joint bracket, for use with side fix bracket B when jointing tracks, galvanized pressed steel
- > D Soffit fixing bracket, open, 51 x 70 mm, for parallel and cross ear applications, galvanized pressed steel
- > E Closed end piece, unhandred, 47 x 35 x 40 mm, to convert or to closed end bracket, galvanized pressed steel
- > F Soffit bracket lock-joint type, 51 x 70 mm, do not over tighten set screws, galvanized pressed steel

Item	2.1 m	3.0 m	Order qty
A Top track	942.51.921	942.51.930	1 pc
Cat. No.			
B Side fixing bracket		942.51.080	1 pc
C Lock joint plate		942.51.082	1 pc
D Soffit fixing bracket		942.51.083	1 pc
E Closed end piece		942.51.084	1 pair
F Soffit bracket lock-joint type		942.51.085	1 pc


Foldaside 240 Endfold trolley hangers



- > Alternate 2 and 4 wheel hangers. Use 4 wheel hanger next to access door
- > Steel, Ø 38 mm plastic wheels, ball bearing lubricated for life
- > Order qty: 1 pc

Item	Cat. No.
G Trolley hanger, 2 wheels	943.20.010
H Trolley hanger, 4 wheels	943.20.011


Foldaside medium duty bottom guiding



- > I Door guide, 30 x 152 x 90 mm, steel angle plate fits rebate of doors, brass roller
- > J Channel, pre-drilled for countersunk screws, bright aluminium
- > Order qty: 1 pc

Door guide	Cat. No.
Item I	943.20.030
Channel	
Item J	2.1 m 3.0 m
	942.51.721 942.51.730

Foldaside light duty bottom guiding



- > K Door guide, 24 x 128 x 154 mm, steel angle fits rebate of door, nylon swivel
- > L Channel, pre-drilled for countersunk screws, bright aluminium
- > Order qty: 1 pc

Door guide	Cat. No.
Item K	943.20.031
Channel	
Item L	2.1 m 3.0 m
	409.14.010 409.14.029