


## Pocket door flush handle, brass



- > Push fit into Ø 25 mm hole
- > Minimum door thickness 35 mm
- > Brass
- > Order qty: 1 pc



Finish	Cat. No.
Polished chrome-plated	901.01.202

## Mortice gravity drop pull handle



- > 130 x 25 x 46 mm
- > Operation: Push to release
- > Light duty
- > Brass
- > Order qty: 1 pc



Finish	Cat. No.
Satin nickel	911.26.131
Polished brass	911.26.130

## Rubber buffer



- > Ø 29 x 11 mm
- > Screw fixing
- > Order qty: 1 pc

	Cat. No.
Rubber buffer	941.60.051

## Sunk slide action flush bolt



- > 200 x 22 mm
- > Maximum depth of cut out 18 mm
- > Principally for use on sliding/folding door systems
- > 16 x 7 mm flat shoot avoids floor channel
- > Fixing to door face only
- > Can accommodate doors 44 mm plus thick dependant on width of floor channel
- > Fixing screws included
- > Grade 316 stainless steel
- > Order qty: 1 pc



Finish	Cat. No.
Satin stainless steel	911.62.350
Polished stainless steel	911.62.351

## Extended throw lever action flush bolt



- > 203 x 25 mm
- > Maximum depth of cut out 38 mm
- > Throw length can easily be adjusted with a screwdriver
- > Flat shoot plate included
- > Brass
- > Order qty: 1 pc



Length	203 mm
Polished brass	900.17.860
Satin nickel	900.17.851
Polished chrome	911.62.470