HXFELE

GROHE RED 2.0 INSTANT HOT WATER TAP

Replace your kettle and get the convenience of kettle-hot water straight from the new Grohe Red Duo mixer tap.

> Grohe Red 2.0 Duo:

Delivers water heated up to 99° instantly. The water is perfect for making tea and coffee, but also filling pots and preparing

Kettle-hot water function activated via the child-safe touch buttons, while standard hot and cold water is controlled via a slim, forward-rotating lever

The high L-shaped spout makes filling pots easy, and it has a swivel range of 150° for further flexibility

Grohe SilkMove ensures smooth, precise lever operation

> Grohe Red 2.0 Mono:

A pillar tap which is the perfect addition to your existing kitchen set-up, designed to sit next to your Grohe Blue or standard kitchen tap, delivering water heated up to 99° at the push of a button

The boiling water function is activated via the child-safe touch

The high L-shaped spout makes filling pots easy, and it has a selectable swivel range of 0°/150°/360° for total flexibility

> Safety is paramount with Grohe Red taps - the mixer features an automatic, illuminated Grohe ChildLock function operated via the touch buttons, and Grohe CoolTouch technology ensures the spout's surface is never too hot to touch



Grohe Red 2.0 Duo kitchen mixer tap and single large boiler, 5.5 litres, L-spout



- > Model: Grohe 303 40
- > 3-in-1: For filtered kettle hot water in addition to standard hot/cold mixed water
- > Max. water temperature inside the boiler: 99°C
- > Only heat as much water as you need saving water, energy and costs
- > Certified safety handle, touch sensitive
- > Tap insulated with Grohe CoolTouch technology
- > Filter system removes heavy metals and organic compounds for fresh filtered kettle hot water
- > Storage heater dims: 491 x 210 mm
- > Storage heater capacity: 5.5 litres
- > Filter system capacity: 600 litres
- > Overall tap height: 378 mm
- > Spout exit reach c/c: 221 mm
- > Spout exit height: 336 mm
- > Control valve type: 35 mm ceramic cartridge
- > Tails included
- > 2.0 bar min. operating pressure
- > 5.0 bar max. operating pressure
- > Brass (polished chrome) or zinc alloy (brushed stainless steel finish)
- > Order qty: 1 pc

2+1 Year	
Guarantee	

Model	Finish	Cat. No.	
303 40 001	Polished chrome	569.24.200	
303 40 DC1	Brushed stainless steel	569.24.000	

Order compression fitting adaptor 569.25.999 separately, shown on page 381A