


# LOOX5 24V LED 3099 STRIP LIGHT SET

Ideal for wardrobes, storage spaces, display cabinets and bathrooms.





- > Light opening on the narrow side, LED points not visible
- > Delicate groove (width 4 mm) and flat surface, shelves remain adjustable
- > Wave and circular shaped installation possible (radius min. 30 mm)
- > Can be split once: Both pieces with separate lead
- > Splash proof for use in wet rooms

## Loox5 24V LED 3099 strip light with silicone sleeve set, 4 mm, IP44 rated



833.75.260 or  
833.75.263  
LED 3099 strip light



833.75.935 Driver



833.89.000  
UK Moulded  
plug

- > For recess mounting, press-fit in 4 x 10 mm groove
- > Can be shortened every 25 mm
- > Voltage: 24V. Wattage: See table below
- > Dimmable
- > Degree of protection: IP44
- > Tube width: 10 mm
- > Tube height: 4 mm
- > Section length: 50 mm
- > Bending radius min. : 30 mm
- > Matt silicone strip, 120 diodes per meter
- > With 2x 0.2 m soldered lead 3.5 A/20 AWG (1 each on the left/right of the strip)
- > Set consists of
  - 1x 833.75.260 or 833.75.263 24V LED 3099 strip light
  - 1x 833.75.935 24V LED driver with socket for switch
  - 1x 833.95.718, lead for connecting LED strip light monochromatic
  - 1x 833.89.000 mains lead moulded plug, 250V
- > Order qty: 1 set



Output:	2700 K	5000 K
Light colour:	Warm white	Cool white
Max. strip length (visual) M;	3	3
Wattage (W/m):	9.6	9.6
Energy efficiency:	<b>A++ G</b>	<b>A++ G</b>
Number of diodes	240	360
Light output (lm/m):	500	540
Efficacy (lm/W):	52	56
CRI Ra / R9:	90 / 50	90 / 50



IP44



Length	2700 K	5000 K
3000 mm	833.88.961	833.88.940



Maximum strip length (visual) describes a strip section with a visually imperceptible drop in luminous flux of max. 30%. Please note: A strip section with a new power supply that follows immediately is noticeably brighter. Max. wattage-dependent strip length on the driver, see technical data for LED strip lights

## YOU ALSO NEED:



**SWITCH**  
Page 5.160-166

**OPTIONAL ACCESSORIES**  
Pages 5.158-159, 5.167-168, 5.178-181

PAGE AMENDED  
14.06.24/3

# LOOX 24V LED 3042 FLEXIBLE STRIP LIGHT SET

This 5 m LED 3042 strip light with 600 LEDs is ideal for direct and extremely homogenous lighting of furniture. Corner connectors are available for 90° installation. Can be shortened every 50 mm.




Aluminium profiles are available to order separately, shown from page **5.184**



## Loos 24V LED 3042 flexible strip light set, 8 mm width



833.70.256 or 833.70.259  
LED 3042 strip light



— Cut LED strip light to length (one contact side remains on the remainder piece; reusable)

— Connect LED strip lights (two contact sides required)

C = section length = 50 mm

P = length of contact surface = 4.0 mm



- > Maximum strip length is dependant on driver wattage capacity, shown on page **5.76**
- > Maximum recommended strip light length for optimum visual light output: 12.0 m

- > Equipped with high quality Samsung LEDs
- > For surface mounting, self adhesive, 5 m length
- > Can be shortened every 50 mm
- > Voltage: 24V. Wattage: 24W (4.8W per metre)
- > Dimmable
- > Degree of protection: IP20
- > Lifetime: >50,000 h
- > Width: 8 mm
- > Height: 1.3 mm
- > With 2.0 m lead with Loos 24V connector
- > White plastic
- > Set consists of
  - 1x 833.76.316 or 833.76.319 24V LED 3042 strip light
  - 1x 833.75.935 24V LED driver with socket for switch
  - 1x 833.89.000 mains lead moulded plug, 250V
  - 1x 833.95.706 lead for connecting LED strip light monochromatic
- > Order qty: 1 set



Output:	2700 K	5000 K
Light colour:	Warm white	Cool white
Wattage (W/m):	4.8 per metre	4.8 per metre
Energy efficiency:	<b>A G</b>	<b>A F</b>
Number of diodes	120 per metre	120 per metre
Light output (Lm/m):	440	495
Efficacy (Lm/W):	92	103
CRI Ra / R9:	90 / 50	90 / 50

24V



IP20



Length	2700 K	5000 K
5 m	833.88.941	833.88.942

## YOU ALSO NEED:



**SWITCH**  
Pages 5.79-86

**ADDITIONAL LEADS**  
Page 5.88

**OPTIONAL ACCESSORIES**  
Pages 5.77, 5.78


PAGE AMENDED  
17.04.25/5

# LOOX COMPATIBLE 24V LED POLAR FLAT LIGHT SET

The Polar light is mounted in a super thin aluminium profile which means you have all the aesthetic appearance of a recessed light but without the work; simple to install by surface mounting and screw fixing.




## Loox Compatible 24V LED Polar flat downlight set, 70 x 190 mm



833.04.130 or 833.04.131  
Polar flat downlight

833.04.210 or 833.04.211  
Polar flat downlight



833.88.757  
Driver



4x adaptors included for  
Loox system compatibility



833.89.000  
UK Moulded  
plug

- > 4 mm flat profile, for surface mounting
- > Screw fixing
- > Voltage: 24V. Wattage: 5W
- > Dimmable
- > Degree of protection: IP20
- > With 2.0 m lead with Loox 24V connector
- > Aluminium
- > Set consists of
  - 3x 833.04.130, 833.04.131, 833.04.210 or 833.04.211 Polar flat downlight
  - 1x 833.88.757 24V LED driver with socket for switch
  - 1x 833.89.000 mains lead moulded plug, 250V
- > Order qty: 1 set



Output:	3100 K	4000 K
Light colour:	Warm white	Cool white
Wattage (W):	5	5
Energy efficiency:	A++	A++
Number of diodes:	24	24
Light output (Lm):	375	400
Efficacy (Lm/W):	75	80
Colour Rendering Index:	> 80	> 80

24 V	0-100%	IP20	Fixings included
Finish	3100 K	4000 K	
Silver anodised	833.88.943	833.88.944	
Black	833.88.945	833.88.946	

## YOU ALSO NEED:




SWITCH  
Pages 5.79-86



OPTIONAL ACCESSORIES  
Pages 5.77, 5.78


# LOOX5 24V LED 3112 SPOT LIGHT, MONOCHROME




## Loox5 24V LED 3112 spot light set, Ø 61 mm



833.75.436 or 833.75.438 Stainless steel coloured spot light



833.72.804 Stainless steel coloured bezel



833.75.933 Driver



833.89.000 UK Moulded plug

- > High quality metal housing
- > Large variety of colours and surfaces
- > Homogeneous illumination
- > For recess mounting, press-fit in Ø 55 mm hole
- > 1.0 mm rim, min. 14 mm hole depth required
- > For surface mounting order bezel separately
- > Voltage: 24V. Wattage: 3W
- > Dimmable
- > Degree of protection: IP20
- > With 2.0 m lead with Loox5 24V connector
- > Set consists of
  - 3x 833.75.436 or 833.75.438 Spot light
  - 3x 833.72.804 Bezel
  - 1x 833.75.933 24V LED driver with socket for switch
  - 1x 833.89.000 mains lead moulded plug, 250V
- > Aluminium housing
- > Order qty: 1 pc



Output:	3000 K	3000 K
Light colour:	Warm white	Cool white
Wattage (W):	3	3
Energy efficiency:		
Number of diodes	12	12
Light output (Lm):	220	240
Efficacy (Lm/W):	73	80
CRI Ta / R9	92 / >50	92 / >50



Finish	3000 K	5000 K
St. steel coloured	833.88.947	833.88.948

## YOU ALSO NEED:



**DRIVER**  
Pg 5.157



**SWITCH**  
Page 5.160-166

**OPTIONAL ACCESSORIES**  
Pages 5.158-159, 5.167-168, 5.178-181

PAGE AMENDED  
27.05.25/3



# LOOX 24V LED 3090 DOWNLIGHT SET, MODULAR, Ø 32.5 MM

Modular downlight - order from choice of four bezel designs in three finishes for surface mounting, or recess mount in Ø 26 mm hole. Downlight includes Samsung LEDs and has a narrow beam angle for staging objects.



## Loox5 24V LED 3090 downlight set, Ø 32.5 mm




833.75.170 or 833.75.173 Silver coloured downlight

### Modular design -

Round or square, surface or recess mounting bezels.  
Lead included



833.89.240 or 833.89.236 Anthracite or silver coloured round bezel



Surface mounting, round

- > Equipped with high quality Samsung LEDs
- > With narrow beam angle for staging objects
- > For recess mounting, press-fit in Ø 26 mm hole, 1.7 mm rim, min. 11 mm hole depth required
- > Voltage: 24V. Wattage: 1.2W
- > Dimmable
- > Degree of protection:
  - IP44 as recess mounted downlight
  - IP20 as surface mounted downlight
- > With 2.0 m lead with Loox5 24V connector
- > Aluminium housing
- > Set consists of
  - 3x 833.75.170 or 833.75.173 Downlight
  - 3x 833.89.240 or 833.89.236 Round bezel
  - 1x 833.75.933 24V Loox5 eco driver with socket for switch
  - 1x 833.89.000 mains lead moulded plug, 250V
- > Order qty: 1 set



833.75.933 Driver



833.89.000 UK Moulded plug

Output:	2700 K	5000 K
Light colour:	Warm white	Cool white
Wattage (W/m):	1.2	1.2
Energy efficiency:		
Number of diodes:	1	1
Light output (Lm):	75	85
Efficacy (Lm/W):	63	71
CRI:	90	90

5 24V



Bezel finish	2700 K	5000 K
Anthracite	833.88.949	833.88.953
Silver coloured	833.88.950	833.88.951

## YOU ALSO NEED:



### SWITCH

Page 5.160-166

### OPTIONAL ACCESSORIES

Pages 5.158-159, 5.167-168, 5.178-181

# LOOX5 24V LED 3092 DOWNLIGHT SET, MODULAR, Ø 65 MM

These lights can be used in a variety of different applications thanks to the modular principle with optional bezels for either surface or recess mounting. Snap-in lead gives a connection that is secure but also allows the light to be easily released.



## Loox5 24V LED 3092 downlight set, Ø 65 mm



833.75.174 or 833.75.177 Downlight

### Modular design -


Round, surface or recess mounting bezels



833.72.124 Round version bezel



833.72.513, 833.72.516 or  
833.72.517 Round version bezel




\*valid for multi-white plugs



833.75.933  
Driver



833.95.791 24V Lead



4x adaptors included for  
Loox system compatibility



833.89.000  
UK Moulded  
plug



Degree of protection with housing  
for undermounted light is IP20

- > Equipped with high quality Samsung LEDs
- > For recess mounting, press-fit in Ø 58 mm hole  
2.6 mm rim, min. 13.5 mm hole depth required
- > For surface mounting
- > Voltage: 24V. Wattage: 3.4W
- > Dimmable
- > Degree of protection:  
IP44 as recess mounted downlight  
IP20 as surface mounted downlight
- > Lead not included, must be ordered separately
- > Silver coloured aluminium housing
- > Set consists of  
3x 833.75.174 or 833.75.177 Downlight  
3x 833.72.124, 833.72.513, 833.72.516 or 833.72.517 Round bezel  
3x 833.95.791 Lead, 2000 mm  
1x 833.75.933 24V LED Eco driver with socket for switch  
1x 833.89.000 mains lead moulded plug, 250V
- > Order qty: 1 set



Output:	2700 K	5000 K
Light colour:	Warm white	Cool white
Wattage (W):	3.4	3.4
Energy efficiency:		
Number of diodes:	6	6
Light output (Lm):	220	260
Efficacy (Lm/W):	65	76
Colour Rendering Index:	>90	>90

5 24 V



Bezel finish	2700 K	5000 K
Silver	833.88.952	833.88.959
Black	833.88.954	833.88.957
Brass	833.88.955	833.88.958
Copper	833.88.956	833.88.960

## YOU ALSO NEED:



**SWITCH**  
Page 5.160-166

**OPTIONAL ACCESSORIES**  
Pages 5.158-159, 5.167-168, 5.178-181

PAGE AMENDED  
23.05.25/3