BATAVIA T-RAXX MULTI PLUNGE SAW 1400W

All major functions are activated via the intuitive mode selector barrel.





T-RAXX Ø 165 mm multi plunge saw, 1400W



- > Electronic variable speed, constant speed and soft start
- > Anti kick back brake
- > Track adjustment
- > Guide rail lock
- > Scribing function (2.5 mm)
- > Easy blade change
- > Festool® and Makita® track compatible
- > Max. cut depth 90° with track: 54 mm
- > Max. cut depth 90° w/o track: 54 mm
- > Max. cut depth 45° with track: 38 mm
- > Max. cut depth 45° w/o track: 42 mm
- > Bevel range: 0° to 48°
- > Blade diameter: Ø 165 mm
- > Arbor: Ø 20 mm
- > Dust extraction adaptor
- > Set consists of: T-RAXX plunge saw 1x TCT saw blade, Ø 165 mm In aluminium case
- > Order qty: 1 set

Item	Cat. No.
Plunge saw	000.47.010



- > Set consists of: 2x Track, 800 mm length
- > Order qty: 1 set

Item	Cat. No.
Track set	000.47.020

T-RAXX track connectors



- > For joining T-RAXX tracks to extend overall track length
- > Order qty: 1 pair

Item	Cat. No.
Track connectors	000.47.021

T-RAXX angle guide



- > Use to give precise mitre cuts for angles set from -55° over 0° to 55° with the curved angle scale
- > Alternatively, the mitre angle limit stop can be installed on the guide rail in such a way that the pre-punched angle settings 0°, 15°, 30° and 45° can be used
- > Order qty: 1 pc

Item	Cat. No.
Angle guide	000.47.022

T-RAXX work clamps



- > To secure T-RAXX track on the work piece
- > Order qty: 1 pair



> Please note: Each clamp requires 25 mm of track length

Item	Cat. No.
Work clamps	000.47.023

T-RAXX Ø 165 mm TCT saw blade



- > Ø 165 mm x Ø 20 mm x 2.2 mm
- > Carbide tipped blade
- > Cuts aluminium, hardwood, softwood, laminate, plastics
- > 48 teeth
- > Order qty: 1 pc

Item	Cat. No.
TCT saw blade	000.49.940

PAGE AMENDED 18.09.19/1