

Track safety hiker boot



- > CE spec. EN ISO 20345:2011 S1P HRO SRC
- > Hardwearing rubber toe buffer with recessed stitching
- > Reflective heel inserts
- > Ankle support system
- > Padded, moisture wicking and highly breathable lining
- > VS100 twin shock absorbing footbed, contoured supports to cradle foot
- > 200 joule wide fitting composite toe cap, non sparking and thermal insulating
- > Flexible woven composite midsole, pierce resistant to 1100N
- > High slip resistance
- > Anti-static and abrasion resistant
- > Heat resistant to aprox. 300°C
- > Acid, alkali, oil and hydrocarbon resistant
- > Shock absorbing heel
- > Suede leather/mesh upper, triple-density phylon/rubber sole
- > Order qty: 1 pair

Size	Cat. No.
6	007.47.910
7	007.47.911
8	007.47.912
9	007.47.913
10	007.47.914
11	007.47.915

Elk safety D-ring boot



- > CE spec. EN ISO 20345:2011 S1P SRA
- > Padded, moisture wicking and highly breathable lining
- > Full length EVA comfort footbed
- > 200 joule wide fitting composite resistant steel toe cap
- > Flexible composite resistant steel, pierce resistant to 1100N
- > Heat resistant to aprox. 150°C
- > Anti-static
- > Acid, alkali, oil and hydrocarbon resistant
- > Ladder grips
- > Shock absorbing heel
- > Grain leather, dual-density polyurethane sole
- > Order qty: 1 pair

Size	Cat. No.
6	007.47.900
7	007.47.901
8	007.47.902
9	007.47.903
10	007.47.904
11	007.47.905

Rawhide safety dealer boot



- > CE spec. EN ISO 20345:2011 SBP HRO SRA
- > Durable, water resistant and breathable
- > Reinforced leather pull on tabs
- > Dual layer elastic and triple stitched seams
- > Fully bound top band
- > Moisture wicking and highly breathable lining
- > VS102 full length replacable, energy return footbed incorporating rebound foam with air circulation vents and anti-bacterial properties
- > 200 joule wide fitting composite resistant steel toe cap
- > Flexible corrosion resistant steel, pierce resistant to 1100N
- > High slip resistance
- > Anti-static and abrasion resistant
- > Heat resistant to aprox. 300°C
- > Acid, alkali, oil and hydrocarbon resistant
- > Powerflex sole, flexibility and anti-fatigue properties
- > Rugged oil stuffed hide, nitrile rubber sole
- > Order qty: 1 pair

Size	Cat. No.
6	007.47.610
7	007.47.611
8	007.47.612
9	007.47.613
10	007.47.614
11	007.47.615

Rocky safety waterproof hiker boot



- > CE spec. EN ISO 20345:2011 S3 HRO SRC
- > Waterproof lining that breathes to reduce perspiration
- > VS102 full length replacable, energy return footbed incorporating rebound foam with air circulation vents and anti-bacterial properties
- > 200 joule wide fitting composite toe cap, non sparking and thermal insulating
- > Flexible woven composite midsole, pierce resistant to 1100N
- > Anti-static and abrasion resistant
- > Heat resistant to aprox. 300°C
- > Acid, alkali, oil and hydrocarbon resistant
- > Shock absorbing defined heel for safety when working on steps/ladders
- > Zip side for easy access
- > Relaxed oiled full grained hide, triple-density phylon/rubber sole
- > Order qty: 1 pair

Size	Cat. No.
6	007.47.920
7	007.47.921
8	007.47.922
9	007.47.923
10	007.47.924
11	007.47.925