

FESTOOL KAPEX COMPOUND MITRE SAW



Festool KS 120 EB GB Kapex circular sliding compound mitre saw



- > Special cutting position, for material up to 120 mm in height
- > Stress-free working with bevel and dual-line laser
- > Simple, precision cutting angle adjustment
- > Fine inclination angle adjustment and rotary base
- > Precision adjustment of tilt and rotation angles
- > Lightweight, compact design
- > Dual-line laser
- > Precise marking of the cutting width
- > Position the workpiece from the left or right side
- > FastFix saw blade changing system
- > Technical data

Power consumption: 1600 W
 Idle engine speed: 14-3400 min⁻¹
 Saw blade diameter: Ø 260 mm
 Cutting depth 90°/90°: 305 x 88 mm
 Cutting depth 45°/90°: 215 x 88 mm
 Cutting depth 50°/90° Left: 196 x 88 mm
 Cutting depth 60°/90° Right: 152 x 88 mm
 Cutting depth 45°/45° Left: 215 x 55 mm
 Cutting depth 45°/45° Right: 215 x 35 mm
 Special cutting depth 90°/90°: 60 x 120 mm
 Special cutting depth 45°/90° Left: 40 x 120 mm
 Special cutting depth 45°/90°: 20 x 120 mm
 Crown moulding diagonal cut at 90°/90°: 168 mm
 Crown moulding diagonal cut at 45°/90°: 168 mm
 Inclination angle: 47/47°
 Mitre angle: 50/60°
 Bench height (on MFT): 923 mm
 Dimensions (WxDxH): 713 x 500 x 470 mm
 Connection Ø d/e: 27/36 mm
 Weight: 21.5 kg

- > Scope of delivery:
 - HW universal saw blade W60
 - Bevel
 - Workpiece clamp
 - Operation tool
 - In a carton
- > Order qty: 1 set

Voltage
240V

Cat. No.
000.50.100