

## Festool CTL 26E GB mobile dust extractor



- > Electronic control for continuously variable suction force
- > Integrated electric socket with automatic electronic on/off switch
- > Compact design gives high mobility
- > Space-saving storage for hose and cable
- > Anti-static function prevents charging with static electricity
- > For NON hazardous dusts
- > Systainer port on top of machine
- > Technical data
  - Power consumption: 350 - 1200 W
  - Airflow max.: 3900 l/min
  - Max. vacuum: 24000 Pa
  - Filter surface area: 3060 cm<sup>2</sup>
  - Rubber-insulated mains cable: 7.5 m
  - Container/filter bag capacity: 26/24 l
  - Dims. (L x W x H): 630 x 365 x 540 mm
  - Max. appliance socket connected load: 2400 W
  - Weight: 13 kg
- > Supplied with:
  - 1x Filter bag
  - Suction hose Ø 27 mm x 3.5 m-AS
  - Hose handle
  - Cable holder
- > Order qty: 1 set

Voltage	Cat. No.
240V	008.53.505
110V	008.53.504
Replacement parts	
Self clean filter bags, 1 set = 5 bags	008.53.380

## Festool Cleantec CTM 26 E GB



- > Approved for dust category M
- > Antistatic function prevents static developing during work
- > Constantly high suction because of the compact high performance turbine
- > Attachment of Systainers via Sys-Dock
- > Hose garage and cable wind up for the greater tidiness and safety
- > Economical because of the optimal use of the available volume with a self clean filter bag in the container
- > Technical data
  - Power consumption: 350-1200 W
  - Airflow max.: 3900 l/min
  - Max. vacuum: 24000 Pa
  - Filter surface area: 6318 cm<sup>2</sup>
  - Rubber-insulated mains cable: 7.5 m
  - Container/Filter bag capacity: 26/24 l
  - Dims (L x W x H): 630 x 365 x 540 mm
  - Max. appliance socket connected load: 2400 W
  - Weight: 13.9 kg
- > Supplied with:
  - 1x Filter bag
  - Suction hose Ø 27 mm x 3.5 m-AS
  - Hose
  - Cable holder
- > Order qty: 1 pc

Voltage	Cat. No.
240V	008.53.508