

FESTOOL ROUTERS

Festool OF 2200 EB Plus router set



- > Applications: Rebating, grooving and profiling. Routing large cutouts, circles and arcs with the multi-routing system MFS. Creating worktop corner joints with the worktop system APS. Routing seals and espagnolettes in windows and doors. Flush trimming, making cutouts, grooving, profiling of mineral material. Creation of string-boards in hardwood or softwood. Stationary routing with the bench-mounted router TF 2200 up to router bit Ø 60 mm
- > Top power development and fully variable speed for hard materials and increased material thicknesses
- > Precise work with little effort thanks to a guide bar support offset by 30°
- > Tool-free copying ring and base-runner change
- > Fast, convenient router-bit change with rocker and ratchet principle
- > Greater precision through extreme torsional rigidity thanks to double guide column clamp
- > Simple and exact routing depth setting to 1/10 mm
- > Fast profile cutter adjustment through coupleable/decoupleable base plate
- > Dust extraction of up to 99% during edge routing through adjustable extraction ring and chip catcher
- > Scope of delivery:
 - > Ø 8 mm clamping collet
 - > Ø 12 mm clamping collet
 - > Ø 1/2" clamping collet
 - > Copying ring Ø 30 mm
 - > Chip deflector
 - > Accessories Systainer
 - > Operation tool
 - > In a generation 3 SYSTAINER
- > Order qty: 1pc

Technical data	
Power consumption	2200 W
Plunge depth	80 mm
Idling speed (rpm)	10000 - 22000
Max. cutter diameter	Ø 89 mm
Fine adjustment	1/10 mm
Connection for dust extraction	Ø 36 mm (27 mm)
Weight	7.8 kg

Voltage	Cat. No.
240V	002.15.007