Festool Angle attachment AN-UNI





attachment no longer needs to be released from the machine Technical data:

in narrow places

> Max. screw size for softwood: 10 x 300 mm

> Holder: FastFix

> Order qty: 1 pc



For TPC 18/4, TDC 18/4 and all Festool C and T cordless drills with FastFix fixture (except CXS/TXS)

Model	Cat. No.
Angle attachment AN-UNI	005.25.318

> For absorbing higher torques and for angular drilling and screwdriving

> Quick angle adjustment simply by rotating the green ring - the

Festool Eccentric attachment EX-UNI



> For drilling and screwdriving close to edges

> Quick angle adjustment simply by rotating the green ring - the attachment no longer needs to be released from the machine

Technical data:

> Max. screw size for softwood: 6 x 100 mm

> Holder: FastFix > Order qty: 1 pc



For TPC 18/4, TDC 18/4 and all Festool C and T cordless drills with FastFix fixture (except CXS/TXS)

	Cat. No.
Eccentric attachment EX-UNI	005.25.319

Festool Keyless chuck KC 13-1/2 MMFP





> Impact-resistant, metal ring, with additional locking device

Technical data:

> Clamping range: 1.5-13 mm

> Holder: FastFix > Order qty: 1 pc



For all Festool cordless drills, cordless percussion drills, drills (except DR 20/DRP 20) and percussion drills with CENTROTEC interface

	Cat. No.
Keyless chuck KC 13-1/2 MMFP	005.25.320

Festool Auxiliary handle AHS-43/230



- > For absorbing higher torques, with additional protection against accidental unscrewing
- > With soft grip

Technical data:

> Holder Ø: 43 mm > Length: 230 mm

> Order qty: 1 pc



For all Festool QUADRIVE TPC 18/4 percussion drils and TDC 18/4 drills

	Cat. No.
Auxiliary handle AHD-43/230	005.25.321