

KBT600XE

Product family: Hood
 Subfamily: Decorative wall hood
 Aesthetics: Neutral
 Design: T flat
 Width category: 60cm
 Extraction: Expulsion
 Electronic control
 Material: Stainless steel
 Color: Stainless steel
 Type of steel: Brushed
 EAN code: 8017709286613
 Hood width: 60 cm



Aesthetics

Logo: Silk screen

Controls

Control setting: Electronic buttons

Programs / Functions

No. of speeds: 3
 Intensive speed
 24h air filter function
 Time-setting options: Automatic switch-off

Technical Features

No. of lights: 2
 Light type: LED
 Light Power: 1,3 W
 Light color temperature scale (°K): 3000 °K
 Free outlet maximum capacity: 820 m³/h
 Motor power: 230 W
 No. of filters: 2
 Anti-grease filters: Aluminium

Filter replacement indicator
 Vent outlet: 150 mm
 Minimum distance from ELECTRIC hob: 500 mm
 Minimum distance from GAS hob: 650 mm
 Non return valve

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	260	49
Speed 2	358	57
Speed 3	473	64
Intensive speed	686	72

Accessories Included

Tube reduction

Performance / Energy Label

Annual Efficiency Consumption (AEChood): 53 kWh/year
 Energy efficiency class (EEC): A
 Fluid Dynamic Efficiency (FDE): 29.8
 Fluid Dynamic Efficiency class (FDEC): A
 Lighting Efficiency (LE): 70.4
 Lighting Efficiency Class (LEC): A
 Grease Filtering Efficiency (GFE): 79.7 %
 Grease Filtering Efficiency Class (GFEC): C
 Air flow at minimum speed (Qmin): 261 m³/h
 Air flow at maximum speed (Qmax): 473 m³/h
 Air flow at boost speed (Qboost): 686 m³/h
 Airborne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 48 dB(A)
 Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 63 dB(A)
 Airborne acoustical A-weighted sound power emission at

boost speed (SPEboost): 71 dB(A)
 Power consumption in stand-by mode (Ps): 0.23 W
 Time increase factor (F): 0.9
 Energy Efficiency Index per first cavity: 52.0
 Measured air flow rate at best efficiency point (Qbep): 395 m³/h
 Measured air pressure at best efficiency point (Qbep): 451 Pa
 Measured electric power input at best efficiency point (Wbep): 159 W
 Normal Power of the light system (WI): 3 W
 Average illumination of the light on the cooking surface (Emiddle): 156
 Sound power level at highest setting (Lwa): 70 dB(A)


Electrical Connection

Electrical connection rating: 230 W
 Voltage: 220-240 V
 Frequency (Hz): 50-60 Hz
 Power supply cable length: 1500 mm

Accessories not included



KITCEKBT
 Chimney extension, dimensions 261,5 * 260 * 830 mm suitable for T-shape hood KBT* & KBCT*, max height 1380 mm
 Stainless Steel



KITFCKBT
 1 pcs di filtro a carboni attivi per i modelli di cappe KBT* / KBCT*



KITFCKBTR
 1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 20 times. dimension 237,5(H)x245x10 mm

