- To be screwed into dowels or sleeves B to F
- For Ø 5, Ø 8 or Ø 10 mm holes
- For single and double sided constructions


A Rafix connecting bolt

- With M4 thread, for screwing into dowels or
- For direct screw-in installation in Ø 5 mm holes or for press-fit installation in Ø 8 or Ø 10 mm holes when used with dowels E or F

Finish Cat. No.	
Bright	263.21.111
Galvanized	263.21.817

Order qty: Multiples of 100 pcs





= Combination slot

Tighten with cross-slot screwdriver size or flat bladed screwdriver


B Sleeve, M4 internal thread

- For Ø 5 mm holes
- · Bright brass

Length	Cat. No.
8 mm	051.45.004

Order qty: Multiples of 100 pcs






C Sleeve


- With M4 internal thread, for press-fit installation in Ø 5 mm holes
- Suitable for double-sided constructions
- Steel

Length	15 mm	18 mm	22 mm	30 mm
Bright	267.00.011	267.00.012	267.00.013	267.00.016
Galvanized	267.00.911	267.00.912	267.00.913	267.00.916

Order qty: Multiples of 100 pcs








D End screw, pan head

- With M4 thread and combination slot
- For screwing into sleeve C for single-sided constructions
- Drive: PZ2 cross slot
- Nickel-plated steel

Length	8 mm	10 mm
Cat. No.	020.92.711	020.92.720

Order qty: Multiples of 100 pcs



E Glue in sleeve, M4 internal thread

- For Ø 8 mm holes
- Will accept connecting bolts with special thread A
- Plastic

Length	8 mm	10 mm
Cat. No.	039.33.140	039.33.042

Order qty: Multiples of 100 pcs





TCH 2013, © Häfele U.K. Ltd 2013. Dimensional data not binding. We reserve the right to alter specifications without notice



F Glue in sleeve, M4 internal thread

- For Ø 10 mm holes
- Will accept connecting bolts with special thread A
- Plastic

Length	10 mm	13 mm
Cat. No.	039.33.239	039.33.033

Order qty: Multiples of 100 pcs





