

Round pipe to flat duct convertor



- > Connects flat ducts to components with round configuration such as wall vents and cooker hood spigots
- > Can be connected to flexhose via threaded hose coupler
- > Flame retardant white material
- > Order qty: 1 pc

System	Cat. No.
System 4 to system 4a	565.30.780
System 5 to system 5a	565.30.782
System 6 to system 6a	565.30.784

Flat duct



- > Can be concealed behind cornice, in ceiling voids or cavity walls
- > Connects to all rectangular component sockets
- > Available in two lengths: 1 m and 1.5 m
- > Flame retardant white PVC
- > Order qty: 1 pc (1 pc = 1 or 1.5 m length)

Length	System 4a	System 5a	System 6a
1000 mm	565.30.730	565.30.732	565.30.734
1500 mm	565.30.731	565.30.733	565.30.735

Flat duct connector



- > Straight connector between two lengths of flat duct
- > Flame retardant white material
- > Order qty: 1 pc

System	Cat. No.
System 4a	565.30.740
System 5a	565.30.742
System 6a	565.30.744

Horizontal 90° bend connector



- > Connects two sections of flat duct at right angles - horizontal to horizontal
- > Flame retardant white material
- > Order qty: 1 pc

System	Cat. No.
System 4a	565.30.750
System 5a	565.30.752
System 6a	565.30.754



- > System **4** = approx Ø 100 mm (internal dimension)
- > System **5** = approx Ø 120 mm (internal dimension)
- > System **6** = approx Ø 150 mm (internal dimension)