
LOOX MODULAR SWITCHES, FOR SNAP-IN CONNECTION

Where switches are not in-built or included choose from the wide range of Loox switches shown here. These Ø 12 mm switches can be recessed or surface mounted with the housings shown on page 109.

Loox sensor switch, modular - touch-free soft on/off switching





- Drill hole Ø 12 mm
- Sensor range: 0-80 mm. Power consumption ≤0.3 W
- Plastic
- Order qty: 1 pc


12V 24V 350mA IP20 7 YEARS

On/off state is stored without the need for power supply (memory function)

Finish	Cat. No.
Silver coloured	833.89.127

Loox door sensor switch, modular - soft on/off switching






- Drill hole Ø 12 mm
- Sensor range: 0-100 mm. Power consumption ≤0.3 W
- Plastic
- Order qty: 1 pc

12V 24V 350mA IP20 7 YEARS

Finish	Cat. No.
Silver coloured	833.89.128

Loox motion detector switch, modular - automatic on/off switching






- Drill hole Ø 12 mm
- Sensor range: 0-3000 mm. Power consumption ≤0.1 W
- Sensor angle: 120°
- Delay time: approx. 30 seconds
- Plastic
- Order qty: 1 pc

12V 24V 350mA IP20 7 YEARS

Finish	Cat. No.
Silver coloured	833.89.129

Loox dimmer switch, modular - soft on/off switching





- Drill hole Ø 12 mm
- Power consumption ≤0.3 W
- Sensor range (touchless only): 0-60 mm
- Plastic
- Order qty: 1 pc

12V 24V 350mA IP20 0% 100% 7 YEARS

Dimming value is stored without the need for power supply (memory function)

Finish	With contact	Touchless
Silver coloured	833.89.058	833.89.126

Please order lead with snap-in connector for modular switch to Loox driver separately, shown on page **107B**

TCH DESIGN 2017. © Häfele U.K. Ltd 2017. Dimensional data not binding. We reserve the right to alter specifications without notice.