




Please order screws in multiples of order quantity shown


Spax Wirox screw, countersunk head



- > Fully threaded (*partially threaded)
- > Countersunk head with T star
- > Wirox coated

Ø x Length/Thread	Driver required	Cat. No.	Order Qty
3.5 x 20 mm	TS20	018.57.386	200
3.5 x 25 mm	TS20	018.57.389	200
3.5 x 30 mm	TS20	018.50.091	200
3.5 x 35 mm	TS20	018.50.093	200
3.5 x 40 mm	TS20	018.50.094	200
3.5 x 45 mm	TS20	018.50.095	200
3.5 x 30/18 mm	TS20	018.57.391	200
3.5 x 35/23* mm	TS20	018.57.393	200
3.5 x 40/23* mm	TS20	018.57.394	200
3.5 x 45/30* mm	TS20	018.57.395	200
4.0 x 25 mm	TS20	018.57.419	200
4.0 x 30 mm	TS20	018.50.121	200
4.0 x 35 mm	TS20	018.50.123	200
4.0 x 40 mm	TS20	018.50.124	200
4.0 x 45 mm	TS20	018.50.125	200
4.0 x 50 mm	TS20	018.50.126	200
4.0 x 30/18* mm	TS20	018.57.421	200
4.0 x 35/23* mm	TS20	018.57.423	200
4.0 x 40/23* mm	TS20	018.57.424	200
4.0 x 45/30* mm	TS20	018.57.425	200
4.0 x 50/32* mm	TS20	018.57.426	200
4.0 x 60/35* mm	TS20	018.57.428	100
4.0 x 70/37* mm	TS20	018.57.430	100
4.5 x 40 mm	TS20	018.50.154	200
4.5 x 50 mm	TS20	018.50.156	200
4.5 x 30/17* mm	TS20	018.57.451	200
4.5 x 40/25* mm	TS20	018.57.455	200
4.5 x 50/32* mm	TS20	018.57.456	200
4.5 x 60/37* mm	TS20	018.57.458	100
4.5 x 70/42* mm	TS20	018.57.460	100
5.0 x 30/17* mm	TS20	018.50.181	200
5.0 x 40 mm	TS20	018.50.184	200
5.0 x 50 mm	TS20	018.50.186	200
5.0 x 40/27* mm	TS20	018.57.484	200
5.0 x 50/32* mm	TS20	018.57.486	200
5.0 x 60/37* mm	TS20	018.57.488	100
5.0 x 70/41* mm	TS20	018.57.490	100
5.0 x 80/46* mm	TS20	018.57.491	100
5.0 x 90/61* mm	TS20	018.57.492	100
5.0 x 100/61* mm	TS20	018.57.493	100
6.0 x 120/68* mm	TS20	018.50.525	100
6.0 x 100/61* mm	TS30	018.57.523	100


Spax continuous hinge screw, countersunk head



- > Fully threaded
- > Countersunk head with PZ cross slot
- > Yellox coated

Ø x Length	Driver required	Cat. No.	Order Qty
3.0 x 12 mm	PZ1	018.42.501	100
3.0 x 16 mm	PZ1	018.42.502	100
3.0 x 20 mm	PZ1	018.42.503	100
3.0 x 25 mm	PZ1	018.42.504	100

Spax MDF screw, countersunk head



- > Countersunk head with T star
- > Wirox coated

Ø x Length	Driver required	Cat. No.	Order qty
3.5 x 40 mm	TS15	010.95.001	200
3.5 x 45 mm	TS15	010.95.002	200
3.5 x 50 mm	TS15	010.95.003	200
4.0 x 40 mm	TS20	010.95.004	200
4.0 x 45 mm	TS20	010.95.005	200
4.0 x 50 mm	TS20	010.95.006	200
4.0 x 60 mm	TS20	010.95.007	100
4.5 x 45 mm	TS20	018.90.155	200
4.5 x 50 mm	TS20	018.90.156	200



- > Screwdrivers and driver bits are shown on page 60
- > Imperial to metric screw size conversion chart shown on page 8

TCH TECHNOLOGY 2018, © Hafele U.K. Ltd 2018. Dimensional data not binding. We reserve the right to alter specifications without notice.