HIGH STRENGTH ADHESIVES

CONTACT ADHESIVES - PAGE 91

- > High grab qualities and long open time to allow for repositioning
- > Can be used to bond impervious or non-porous materials together
- They are used in such areas as laminating large surfaces and bonding rubber sheets to other impervious materials such as fibreglass

Häfele adhesive



- > Solvent free adhesive
- > Fast bonding on most common materials at room temperature
- > Ideal for bonding mitre joints in wood and MDF, also bonds ceramics, aluminium, leather, fabric and most plastics
- > Economical to use
- > Replaces traditional fixings such as screws, staples and nails
- > Bottles supplied with nozzle
- > 50 g bottle supplied with stainless steel pin in cap, to keep the nozzle clear and adhesive free
- > Order qty: 1 pc

Size	Cat. No.
50 g, nozzle	003.04.000
500 g, screw cap	003.04.004

Häfele adhesive accelerator aerosol





- > Solvent based activator designed to enhance the cure speed of instant adhesive
- > Reduces fixing times and ensures adhesive is fully cured
- > Seals surface porosity to stop migration of adhesive into the substrate
- > Ideally suited for use with Hafele instant adhesives 003.04.000 and 003.04.004
- > Supplied with straw for improved directional control
- > Order qty: 1 pc

Size	Cat. No.
200 ml	003.04.010

We

data not binding.

TCH TECHNOLOGY 2018, © Häfele U.K. Ltd 2018.