
GRASS TIOMOS 110° SOFT CLOSE HINGES



Tiomos Night - anthracite finish

Nickel-plated finish

Drilling pattern for cup fixing




Dowel/Impresso tool free fixing



fixing also suits above

screw fixing



Minimum gap for doors with chamfered edges (r = 1 mm) with factory setting

> Order fixing screws separately

> For standard applications

details), Ø 35 mm cup

> Click on arm

> Order qty: 1 pc

above, a trial fitting is recommended)

> Available with or without integrated soft close > Screw fixing, dowel or impresso (quick fix) fixing cup

> Tiomos Night, anthracite finish, also available

> Opening angle 110° (can be restricted to 85°, see page 73 for


> For door thickness up to 24 mm (for door thicknesses 24 mm and

> Up to 24 mm overlay using full overlay plus hinge (see page 43)

> Full overlay and full overlay plus mounting has steel cup and hinge arm. Half overlay and inset mounting has steel cup and

Door thickness	Distance to cup E mm					
mm	3.0	4.0	5.0	6.0	7.0	
16	0.6	0.6	0.6	0.6	0.6	
17	0.6	0.6	0.6	0.6	0.6	
18	0.7	0.7	0.7	0.7	0.7	
19	0.9	0.9	0.9	0.9	0.9	
20	1.1	1.1	1.1	1.1	1.1	
21	1.4	1.3	1.3	1.3	1.3	
22	1.6	1.6	1.6	1.5	1.5	
24	2.4	2.1	2.1	2.1	2.0	
	Minimum gap F					

Grass Tiomos 110° concealed hinge, full overlay mounting



Application example with 2 mm mounting plate shown - see table opposite for details

38

Door ove	erlay mm						
13	14	15	16	17	18	19	
		3	4	5	6	7	0
3	4	5	6	7			2
Distance	to cup B	E mm		Мо	unting p	late heid	aht mm







TCH TECHNOLOGY 2018, © Häfele U.K. Ltd 2016.


Soft close	Screw fixing	Impresso	Dowel	
Nickel-plated	l finish			
With	348.31.801	348.31.831	348.31.811	
Without	348.31.601	348.31.631	-	
Tiomos Night - anthracite finish				
With	348.31.805	-	-	



Most of the products you will find in this Directory are available within 24 hours. However, to be able to offer the breadth of range in our collection, a small number of products have a longer lead time that is typically around 14 days. Please call 0800 171 2909 for an accurate delivery date when you see this symbol.

HAFELE

Grass Tiomos 110° concealed hinge, half overlay/twin mounting



Application example with 2 mm mounting plate shown - see table opposite for details

Door ove	erlay mm						
6.5	7.5	8.5	9.5	10.5	11.5	12.5	
		3	4	5	6	7	0
3	4	5	6	7			2
Distance	to cun F	mm		Moi	ıntina nl	ate heir	nht mm




1	GRASS
ı	25
ı	YEAR
	WARRANTY



Soft close	Finish	Screw fixing	Impresso	
With	Nickel-plated	348.31.802	348.31.832	
Without	Nickel-plated	348.31.602	-	
Tiomos Nig	ıht			
With	Anthracite	348.31.806	⊘ -	

Grass Tiomos 110° concealed hinge, inset mounting



Application example with 2 mm mounting plate shown - see table opposite for details

D					
Door gap mm					
4	3	2	1	0	
			3	4	0
	3	4	5	6	2
Distance to cup E mm		Mou	nting pla	ite heig	ht mm








ı	Soft close	Finish	Screw fixing	Impresso
	With	Nickel-plated	348.31.803	348.31.833
	Without	Nickel-plated	348.31.603	-
	Tiomos Nigh	ıt		
	With	Anthracite	348.31.807	-

Grass Tiomos 110° concealed hinge, full overlay plus



reserve the right to alter specifications without notice

TCH TECHNOLOGY 2018, © Häfele U.K. Ltd 2016. Dimensional data not binding. We

Application example with 2 mm mounting plate shown - see table opposite for details

Door ove	rlay mm						
16	17	18	19	20	21	22*	
		3	4	5	6	7	0
3	4	5	6	7			2
Distance to cup E mm			Мо	unting p	late hei	ght mm	

*door overlay from 24 mm, use mounting plate 348.38.560 on page 68







Soft close	Finish	Screw fixing	Impresso	
With	Nickel-plated	348.31.800	348.31.830	
Without	Nickel-plated	348.31.600	-	

YOU ALSO NEED:






OPTIONAL ACCESSORIES
Pages 73-74, 109-121

Grass Tiomos cruciform mounting plate, 4 point fixing






- > For TIOMOS click on fixing hinges only
- > Hospa screw fixing
- > Two part plate with ± 2 mm height adjustment via worm screw
- > Nickel-plated steel
- > Order fixing screws separately
- > Order qty: 1 pc







Height	0 mm	2 mm
Hospa screw	348.38.511	348.38.512