

FSB ASL® ALUMINIUM

A range of modern design lever handles made from aluminium.




FSB ASL® sets new standards with innovative adaptor technology and additional value-adding features. The new adaptor technology makes for extremely simple and rapid assembly because the base rose is screwed to the door leaf first, without either its cover or the handle

- > All in one single set packaging
- > Non-handed
- > Concealed guide ring
- > Spring mechanism
- > Bearing fixed but free to rotate
- > Stainless steel reinforced base
- > M5 stainless steel screw fixing
- > 45° angle of rotation
- > Rapid assembly
- > 20 mm door thickness increments
- > BS EN 1906 class 4 certified
- > Aluminium

FSB ASL® 1021 lever handles, aluminium



- > Pair of lever handles and roses
- > Grub screw fixing on 8 mm Stabil spindle
- > Sprung, for use with standard duty followers
- > To suit doors 39-58 mm thick
- > With spring mechanism
- > Aluminium
- > Order qty: 1 pair




Finish	Cat. No.
Silver anodised aluminium	905.99.170

FSB ASL® 1144 lever handles, aluminium



- > Pair of lever handles and roses
- > Grub screw fixing on 8 mm Stabil spindle
- > Sprung, for use with standard duty followers
- > To suit doors 39-58 mm thick
- > With spring mechanism
- > Aluminium
- > Order qty: 1 pair



Finish	Cat. No.
Silver anodised aluminium	905.99.171



Co-ordinating escutcheons and WC/emergency release also available see page 74