



Phoenix Mild steel, fixed pin, 3 knuckle, shrouded bearing butt hinge, 102 x 76 mm



- > Maximum adjusted door weight 100 kg
- > Minimum door thickness 44 mm
- > Maintenance free
- > 3 knuckle hinge with fixed pin and shrouded bearings
- > Ø 5 x 30 mm wood screws included
- > Approved CF 351 certifiere
- > CE marked
- > BS EN 1935, grade 12
- > Mild steel
- > Order qty: 1 pc



BS EN 1935

4	7	5	1	1	0	0	12
---	---	---	---	---	---	---	----




Finish	Cat. No.
Satin nickel	926.91.466
Zinc-plated	926.91.469

Plain knuckle stainless steel butt hinge, 63 x 38 mm



- > Maximum adjusted door weight 10 kg
- > Minimum door thickness 15 mm
- > Square corners only
- > Grade 304 stainless steel
- > Order qty: 1 pc




➔ Copper finishes are also available to order on request - please contact us for further information

Finish	Satin	Polished
Square corners	921.08.100	926.91.031

Plain knuckle stainless steel butt hinge, 76 x 50 mm



- > Maximum adjusted door weight 20 kg
- > Minimum door thickness 25 mm
- > Square corners only
- > Grade 304 stainless steel
- > Order qty: 1 pc



➔ Copper finishes are also available to order on request - please contact us for further information

Finish	Satin	Polished
Square corners	921.08.104	926.91.061