



LIFT-OFF BUTT HINGES

A lift off hinge is made up of two parts, making it the hinge of choice for applications where doors may need to be removed quickly and easily without opening the door, most commonly used on toilet doors.

Stainless steel, concealed bearing, lift-off hinge, 102 x 76 mm





- > Staggered hole pattern
- > Maximum adjusted door weight 120 kg
- > Minimum door thickness 35 mm
- > Square and radius corners
- > Maintenance free
- > CE marked
- > BS EN 1935, grade 13
- > Grade 304 stainless steel
- > Order qty: 1 pc



Finish	Satin	Polished
Clockwise closing	926.91.240	926.91.241
Anti-clockwise closing	926.91.242	926.91.243

Loadmaster stainless steel lift-off hinge, 102 x 89 mm



- > ANSI hole pattern (template drilled)
- > Maximum adjusted door weight 120 kg
- > Minimum door thickness 44 mm
- > Square and radius corners
- > Maintenance free oilite bush bearings
- > CE marked
- > BS EN 1935, grade 14
- > Grade 316 stainless steel
- > Order qty: 1 pc



Finish	Satin
Square corners	
Clockwise closing	926.91.320
Anti-clockwise closing	926.91.322
Radius corners	
Clockwise closing	926.91.330
Anti-clockwise closing	926.91.332



Most of the products you will find in this catalogue are available within 24 hours. However, to be able to offer the breadth of range in our collection, a small number of products have a longer lead time that is typically around 14 days. Please call 0800 171 2909 for an accurate delivery date when you see this symbol.